

High Delivery Pressure Models

Description: Designed for a wide range of pressure settings, these single-stage regulators are recommended for use in petroleum field applications, research laboratories for hydrogenation, catalytic reduction, accelerated age testing, calorimetric testing, component testing, and pressure testing applications.

These regulators feature a rugged brass piston, which provides increased safety and reliability at high delivery pressures. A 25-micron inlet filter protects internal components.

Special Service

PRESSURE REGULATORS



Y11-N198J/K
Y11-N114G
Y11-N115H



Y11-C198J
Y11-C198K

Design Features

Rugged Brass Piston

provides increased safety and reliability at high delivery pressures.

Bonnet Vent Ports (with optional bonnet vent adaptors)

allow venting of hazardous gases in the event of sensor O-ring failure.

Standard Threaded Bonnet (with optional collar mount nuts)

permits panel mounting.

Ultrasonic Cleaning

allows high-purity gas handling without costly pre-cleaning.

Specifications

Maximum Rated Inlet Pressure	3,000 psig
Outlet Pressure Ranges	0-1000, 0-2,000, 0-4,000, 0-6,000 psig
Flow Capacity	Cv=0.06
Ambient Operating Temperature	-15° F to +165° F
Designed Leak Rate	Bubble-Tight (helium)
Weight	3 lbs
Ports (5)	1/4" FNPT
Outlet	1/4" MNPT Instrument Valve
Decay Inlet Characteristic	1.00/100 psi

Materials

Body	Nickel-Plated Brass
Bonnet	Nickel-Plated Brass
Seat	PCTFE
Piston	Brass
Piston O-Ring	Viton-A®
Backup Ring	PTFE
Gauges	2 1/2" Nickel-Plated Brass
Filter	316 Stainless Steel

Ordering Information

Product Number	Material	Max Inlet Pressure (psig)	Max Outlet Pressure (psig)	Capacity (scfh @ Max Del. Pressure)	Relief Valve Port	Inlet Gauge Range (psig)	Delivery Gauge Range (psig)
Y11-N114G(CGA)	Brass	3,000	1,500	2,500	No	0-4,000	0-2,000
Y11-N115H(CGA)	Brass	3,000	2,500	3,000	No	0-4,000	0-4,000
*Y11-N198J(CGA)	Brass	6,000	4,000	10,000	No	0-10,000	0-6,000
*Y11-N198K(CGA)	Brass	6,000	6,000	10,000	No	0-10,000	0-6,000
*Y11-C198J(CGA)	SS	10,000	4,000	10,000	No	0-10,000	0-6,000
*Y11-C198K(CGA)	SS	10,000	6,000	10,000	No	0-10,000	0-6,000
Y11-C114G(CGA)	SS	4,000	1000	1,270	No	0-4,000	0-2,000
Y11-C115H(CGA)	SS	6,000	2000	1,270	No	0-4,000	0-3,000

*Self venting

Available Options

Product Number	Description
Y99-BONNETADP	Bonnet Vent Adaptor
Y99-CHROMNUT	Panel Mount Nut (2 required)
Y99-750BKT	Wall Mounting Bracket