

## Clever Quick-Mount Option

- Compact Gas Delivery Assembly

**Description:** The Clever Quick-Mount option enables a practical and safe wall-mounted installation of any Analytical, High Purity, or Ultra High Purity cylinder regulator. This allows right-out-of-the box installation of the regulator assembly onto a wall or existing structure. The convenient, compact design significantly minimizes the amount of valuable wall space normally required to wall mount regulators.

Clever Quick-Mount options include 30" stainless steel flexible pigtails, an appropriate wall-mount bracket, a stainless steel street elbow fitting, and a CGA connection with integrated check valve to prevent contaminants from entering the gas delivery supply during cylinder change out. The wall-mount brackets are fabricated from 304 stainless steel for durable, long-life service and are suitable for most environments and locations.

**NOTE:** Not available with Airgas General Purpose Series and Corrosive Service Regulators. Regulator is not included; must be ordered separately.

Specifications	
Max Rated Inlet Pressure	3500 psig
Outlet Pressure Range	-40°F to +165°F
Weight	3 lbs (added to weight of regulator)
Bracket	304 Stainless Steel
Pigtails	30" Corrugated Bellows, 316 Stainless Steel Flex



### Design Features

#### Compact Design

minimizes valuable wall space required to wall-mount regulators

#### Convenient Installation

ready to mount right out of box

#### Increases Speed & Efficiency

eliminates the need to handle regulator during cylinder change-outs

#### Check Valve CGAs

prevents contaminants from entering gas stream

### Ordering Information

Product Number	Regulator Series	No. Supply Cylinders
Y15-QMB1	244, N145, N245, T265	1
Y15-QMB2	244, N145, N245, T265	2
Y15-QMS1	E444, E464, C444, C445, CHP444, CHP445	1
Y15-QMS2	E444, E464, C444, C445, CHP444, CHP445	2

### Available Options

Product Number	Description
Y99-4801201	Block and Vent Assembly; contains and removes all contaminants from entering gas stream
Y99-4EFV(xxx)	Excess Flow Shut-Off Valve; pressure/flow limit must be specified
Y15-4P72K1C	Option for 6 foot pigtail for single cylinder
Y15-4P72K2C	Option for 6 foot pigtail for two cylinders