

Vinyl Chloride (CH₂CHCl)

- Other balance gases and cylinder sizes are available upon request.
- Concentrations over 1.5% are provided at reduced pressure and volume.

Vinyl Chloride in Nitrogen		
Concentration	Cylinder Size	≈Contents ft ³
1 ppm – < 100 ppm	150A	144
	80A	77
	33A	33
100 ppm – 5000 ppm	150A	144
	80A	77
	33A	33

Primary Standards available for concentrations greater than 30 ppm.
Standard Valve Outlet: CGA 350
Certificate of Analysis included.

Technical Data & Shipping Information

Cylinder Pressure	2000 psig
U.S. DOT Class	2.2
U.S. DOT Label	Nonflammable Gas
ID Number	UN1956

Additional Information:

Concentrations up to 5,000 ppm can be certified as above. Higher concentrations are available as standard analyzed gas mixtures.

Vinyl Chloride Mixtures are certified in accordance with Environmental Protection Agency Regulations as cited in the Federal Register, Vol. 41, No. 205, Oct. 21, 1976, and Vol. 42, No. 109, June 7, 1977.

You'll find it with us—a wide range of specialty gas equipment designed especially for gas mixtures.



Pictured: Y11-N145

Equipment Recommendations are found on page 38