



# Nissen High Temperature Metal Marker

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 07/28/2014

Version: 1.0

## SECTION 1: IDENTIFICATION

### Product Identifier

**Product Form:** Mixture

**Product Name:** Nissen High Temperature Metal Marker

**Synonyms:** White Part# 00290, Black Part #00291

**Intended Use of the Product** Not available

### Name, Address, and Telephone of the Responsible Party

#### **Company**

J.P. Nissen Co.

2544 Fairhill Avenue

Glenside, PA 19038

T 215-886-2025 - F 215-886-0707

#### Emergency Telephone Number

**Emergency number** : 1-800-424-9300

## SECTION 2: HAZARDS IDENTIFICATION

### Classification of the Substance or Mixture

#### **Classification (GHS-US)**

Flam. Liq. 3 H226

Muta. 1B H340

Carc. 1B H350

STOT RE 1 H372

Asp. Tox. 1 H304

Aquatic Acute 1 H400

Aquatic Chronic 2 H411

#### Label Elements

##### **GHS-US Labeling**

##### **Hazard Pictograms (GHS-US)**



##### **Signal Word (GHS-US)**

: Danger

##### **Hazard Statements (GHS-US)**

: H226 - Flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H340 - May cause genetic defects  
H350 - May cause cancer  
H372 - Causes damage to organs through prolonged or repeated exposure  
H400 - Very toxic to aquatic life  
H411 - Toxic to aquatic life with long lasting effects

##### **Precautionary Statements (GHS-US)**

: P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/bond container and receiving equipment.  
P241 - Use explosion-proof electrical, ventilating, and lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P260 - Do not breathe vapors, mist, spray.  
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

# Nissen High Temperature Metal Marker

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P270 - Do not eat, drink or smoke when using this product.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection, respiratory protection.  
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P314 - Get medical advice and attention if you feel unwell.  
P331 - If swallowed, do NOT induce vomiting.  
P370+P378 - In case of fire: Use appropriate media to extinguish.  
P391 - Collect spillage.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

### Other Hazards

#### Other Hazards Not Contributing to the Classification:

**Other Hazards:** Flammable vapors can accumulate in head space of closed systems. Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. When heated to decomposition, emits toxic fumes.

**Unknown Acute Toxicity (GHS-US)** Not available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### Substances

Name	Product identifier	% (w/w)	Classification (GHS-US)
Titanium dioxide	(CAS No) 13463-67-7	30 - 40	Not classified
Stoddard solvent	(CAS No) 8052-41-3	33 - 35	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Carbon black	(CAS No) 1333-86-4	1 - 5, 5 - 10	Carc. 2, H351
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with montmorillonite ((Al <sub>1.33</sub> -1.67Mg <sub>0.33</sub> -0.67)(Ca <sub>0</sub> -1Na <sub>0</sub> -1)0.33Si <sub>4</sub> (OH) <sub>2</sub> O <sub>10</sub> .xH <sub>2</sub> O))	(CAS No) 68911-87-5	1 - 5, 5 - 10	Not classified
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	1 - 5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

Multiple WHMIS ranges have been utilized due to varying composition.

Full text of H-phrases: see section 16

## SECTION 4: FIRST AID MEASURES

### Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If exposed or concerned: Get medical advice/attention.

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.

# Nissen High Temperature Metal Marker

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

**Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation persists.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

### **Most Important Symptoms and Effects Both Acute and Delayed**

**General:** May be fatal if swallowed and enters airways. Causes damage to organs through prolonged or repeated exposure. May cause heritable genetic damage. May cause cancer.

**Inhalation:** May cause respiratory irritation.

**Skin Contact:** May cause skin irritation.

**Eye Contact:** May cause eye irritation.

**Ingestion:** May be fatal if swallowed and enters airways. Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** May cause cancer. May cause genetic defects. May cause damage to organs through prolonged or repeated exposure.

### **Indication of Any Immediate Medical Attention and Special Treatment Needed**

If exposed or concerned, get medical advice and attention.

## **SECTION 5: FIRE-FIGHTING MEASURES**

### **Extinguishing Media**

**Suitable Extinguishing Media:** Water spray, fog, carbon dioxide, foam, dry chemical.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### **Special Hazards Arising From the Substance or Mixture**

**Fire Hazard:** Flammable liquid and vapor.

**Explosion Hazard:** May form flammable/explosive vapor-air mixture.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### **Advice for Firefighters**

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides. Oxides of titanium. May liberate toxic gases. May release flammable gases. Sulfur oxides.

**Other information:** Do not allow run-off from fire fighting to enter drains or water courses. Do not allow the product to be released into the environment.

### **Reference to Other Sections**

Refer to section 9 for flammability properties.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **Personal Precautions, Protective Equipment and Emergency Procedures**

**General Measures:** Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid breathing (vapors, mist, spray). Use only outdoors or in a well-ventilated area. Do not allow product to spread into the environment. Avoid all contact with skin, eyes, or clothing.

#### **For Non-Emergency Personnel**

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### **For Emergency Personnel**

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Ventilate area.

### **Environmental Precautions**

Prevent entry to sewers and public waters. Avoid release to the environment.

### **Methods and Material for Containment and Cleaning Up**

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

# Nissen High Temperature Metal Marker

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely. Collect spillage. Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools. Contact competent authorities after a spill.

### Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

## SECTION 7: HANDLING AND STORAGE

### Precautions for Safe Handling

**Additional Hazards When Processed:** Handle empty containers with care because residual vapors are flammable. When heated to decomposition, emits toxic fumes. Use only non-sparking tools.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Wash hands and forearms thoroughly after handling.

### Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Comply with applicable regulations.

**Storage Conditions:** Store in a well-ventilated place. Keep container tightly closed. Keep/Store away from extremely high or low temperatures, ignition sources, combustible materials, incompatible materials.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers.

**Specific End Use(s)** Not available

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

<b>Titanium dioxide (13463-67-7)</b>		
Mexico	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Mexico	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup>
USA IDLH	US IDLH (mg/m <sup>3</sup> )	5000 mg/m <sup>3</sup>
Alberta	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
British Columbia	OEL TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
Manitoba	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Newfoundland & Labrador	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Nova Scotia	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Nunavut	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total mass)
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total mass)
Ontario	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Prince Edward Island	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Québec	VEMP (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica)
Saskatchewan	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Saskatchewan	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Yukon	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Yukon	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
<b>Carbon black (1333-86-4)</b>		
Mexico	OEL TWA (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
Mexico	OEL STEL (mg/m <sup>3</sup> )	7 mg/m <sup>3</sup>
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (Carbon black in presence of Polycyclic aromatic hydrocarbons)
USA IDLH	US IDLH (mg/m <sup>3</sup> )	1750 mg/m <sup>3</sup>

# Nissen High Temperature Metal Marker

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Alberta	OEL TWA (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
British Columbia	OEL TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
Manitoba	OEL TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
Newfoundland & Labrador	OEL TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
Nova Scotia	OEL TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
Nunavut	OEL STEL (mg/m <sup>3</sup> )	7 mg/m <sup>3</sup>
Nunavut	OEL TWA (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (mg/m <sup>3</sup> )	7 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
Ontario	OEL TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
Prince Edward Island	OEL TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
Québec	VEMP (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
Saskatchewan	OEL STEL (mg/m <sup>3</sup> )	7 mg/m <sup>3</sup>
Saskatchewan	OEL TWA (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
Yukon	OEL STEL (mg/m <sup>3</sup> )	7 mg/m <sup>3</sup>
Yukon	OEL TWA (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
<b>Stoddard solvent (8052-41-3)</b>		
Mexico	OEL TWA (mg/m <sup>3</sup> )	523 mg/m <sup>3</sup>
Mexico	OEL TWA (ppm)	100 ppm
Mexico	OEL STEL (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup>
Mexico	OEL STEL (ppm)	200 ppm
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2900 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	350 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
USA IDLH	US IDLH (mg/m <sup>3</sup> )	20000 mg/m <sup>3</sup>
Alberta	OEL TWA (mg/m <sup>3</sup> )	572 mg/m <sup>3</sup>
Alberta	OEL TWA (ppm)	100 ppm
British Columbia	OEL STEL (mg/m <sup>3</sup> )	580 mg/m <sup>3</sup>
British Columbia	OEL TWA (mg/m <sup>3</sup> )	290 mg/m <sup>3</sup>
Manitoba	OEL TWA (ppm)	100 ppm
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	525 mg/m <sup>3</sup>
New Brunswick	OEL TWA (ppm)	100 ppm
Newfoundland & Labrador	OEL TWA (ppm)	100 ppm
Nova Scotia	OEL TWA (ppm)	100 ppm
Nunavut	OEL STEL (mg/m <sup>3</sup> )	720 mg/m <sup>3</sup>
Nunavut	OEL STEL (ppm)	125 ppm
Nunavut	OEL TWA (mg/m <sup>3</sup> )	575 mg/m <sup>3</sup>
Nunavut	OEL TWA (ppm)	100 ppm
Northwest Territories	OEL STEL (mg/m <sup>3</sup> )	720 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (ppm)	125 ppm
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	575 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (ppm)	100 ppm
Ontario	OEL TWA (mg/m <sup>3</sup> )	525 mg/m <sup>3</sup> (140°C Flash aliphatic solvent)
Prince Edward Island	OEL TWA (ppm)	100 ppm
Québec	VEMP (mg/m <sup>3</sup> )	525 mg/m <sup>3</sup>
Québec	VEMP (ppm)	100 ppm
Saskatchewan	OEL STEL (ppm)	125 ppm
Saskatchewan	OEL TWA (ppm)	100 ppm

# Nissen High Temperature Metal Marker

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Yukon	OEL STEL (mg/m <sup>3</sup> )	720 mg/m <sup>3</sup>
Yukon	OEL STEL (ppm)	150 ppm
Yukon	OEL TWA (mg/m <sup>3</sup> )	575 mg/m <sup>3</sup>
Yukon	OEL TWA (ppm)	100 ppm
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>		
British Columbia	OEL TWA (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup> (application restricted to conditions in which there are negligible aerosol exposures)

### Exposure Controls

**Appropriate Engineering Controls:** Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Take precautionary measures against static discharges. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases/vapours may be released. Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical goggles or safety glasses.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** Use NIOSH-approved air-purifying or supplied-air respirator where airborne concentrations of vapor or mist are expected to exceed exposure limits.

**Thermal Hazard Protection:** Wear suitable protective clothing.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Viscous liquid
Odor	: Aromatic odor
Odor Threshold	: Not available
pH	: Not available
Relative Evaporation Rate (butylacetate=1)	: Slower than n-butyl acetate
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: 158.9 - 196.1 °C (318°F - 385°F)
Flash Point	: 43.9 °C (111°F)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: 1 % (Explosive limit)
Upper Flammable Limit	: 7 % (Explosive limit)
Vapor Pressure	: 20.8 mm Hg (@21.1°C (70°F))
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: < 1
Solubility	: Not available
Partition coefficient: n-octanol/water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.

# Nissen High Temperature Metal Marker

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Explosion Data – Sensitivity to Static Discharge** : Static discharge could act as an ignition source.

### SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** Hazardous reactions will not occur under normal conditions.

**Chemical Stability:** Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks. Incompatible materials.

**Incompatible Materials:** strong acids. Strong bases. Strong oxidizers.

**Hazardous Decomposition Products:** Carbon oxides (CO, CO<sub>2</sub>). May release flammable gases. Oxides of titanium. Nitrogen oxides. Sulfur oxides. Toxic vapors.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### Information on Toxicological Effects - Product

**Acute Toxicity:** Not classified

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Not classified

**Serious Eye Damage/Irritation:** Not classified

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** May cause genetic defects.

**Teratogenicity:** Not available

**Carcinogenicity:** May cause cancer.

**Specific Target Organ Toxicity (Repeated Exposure):** Causes damage to organs through prolonged or repeated exposure.

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** May cause respiratory irritation.

**Symptoms/Injuries After Skin Contact:** May cause skin irritation.

**Symptoms/Injuries After Eye Contact:** May cause eye irritation.

**Symptoms/Injuries After Ingestion:** May be fatal if swallowed and enters airways. Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** May cause cancer. May cause genetic defects. May cause damage to organs through prolonged or repeated exposure.

#### Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

<b>Titanium dioxide (13463-67-7)</b>	
LD50 Oral Rat	> 10000 mg/kg
<b>Carbon black (1333-86-4)</b>	
LD50 Oral Rat	> 8000 mg/kg
<b>Stoddard solvent (8052-41-3)</b>	
LD50 Oral Rat	> 5 g/kg Behavioral somnolence
LD50 Dermal Rabbit	> 3 mg/kg
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 5.2 mg/l/4h
<b>Titanium dioxide (13463-67-7)</b>	
IARC Group	2B
<b>Carbon black (1333-86-4)</b>	
IARC Group	2B

# Nissen High Temperature Metal Marker

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 12: ECOLOGICAL INFORMATION

#### Toxicity

**Ecology - General:** Very toxic to aquatic life with long lasting effects.

Carbon black (1333-86-4)	
LC50 Fish 1	5601 mg/l
EC50 Daphnia 1	5600 mg/l (Exposure time: 24 h - Species: Daphnia magna)

Stoddard solvent (8052-41-3)	
LC50 Fish 1	0.42 mg/l

Petroleum distillates, hydrotreated light (64742-47-8)	
LC50 Fish 1	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC 50 Fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

#### Persistence and Degradability

Nissen High Temperature Metal Marker	
Persistence and Degradability	May cause long-term adverse effects in the environment.

#### Bioaccumulative Potential

Nissen High Temperature Metal Marker	
Bioaccumulative Potential	Not established.

Stoddard solvent (8052-41-3)	
Log Pow	3.16 (Octanol/water partition coefficient 3.16/7.06)

Petroleum distillates, hydrotreated light (64742-47-8)	
BCF fish 1	61 - 159

**Mobility in Soil** Not available

#### Other Adverse Effects

**Other Information:** Avoid release to the environment.

### SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.


**Additional Information:** Handle empty containers with care because residual vapors are flammable.

**Ecology – Waste Materials:** This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

### SECTION 14: TRANSPORT INFORMATION

#### 14.1 In Accordance with DOT

Proper Shipping Name : CONSUMER COMMODITY  
Hazard Class : 9  
Identification Number : ID8000  
Label Codes : 9  
ERG Number : 171



#### 14.2 In Accordance with IMDG

Proper Shipping Name : PAINT  
Hazard Class : 3  
Identification Number : UN1263  
Packing Group : III  
Label Codes : 3  
EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-E  
Marine pollutant : Marine pollutant





# Nissen High Temperature Metal Marker

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 14.3 In Accordance with IATA

Proper Shipping Name : CONSUMER COMMODITY  
 Identification Number : ID8000  
 Hazard Class : 9  
 Label Codes : 9  
 ERG Code (IATA) : 9L



### 14.4 In Accordance with TDG

Proper Shipping Name : CONSUMER COMMODITY  
 Hazard Class : 9  
 Identification Number : ID8000  
 Label Codes : 9



## SECTION 15: REGULATORY INFORMATION

### US Federal Regulations

<b>Nissen High Temperature Metal Marker</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard
<b>Titanium dioxide (13463-67-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Carbon black (1333-86-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Stoddard solvent (8052-41-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>SARA Section 311/312 Hazard Classes</b>	Fire hazard Immediate (acute) health hazard
<b>Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with montmorillonite ((Al1.33-1.67Mg0.33-0.67)(Ca0-1Na0-1)0.33Si4(OH)2O10.xH2O)) (68911-87-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

### US State Regulations

<b>Titanium dioxide (13463-67-7)</b>	
<b>U.S. - California - Proposition 65 - Carcinogens List</b>	WARNING: This product contains chemicals known to the State of California to cause cancer.
<b>Carbon black (1333-86-4)</b>	
<b>U.S. - California - Proposition 65 - Carcinogens List</b>	WARNING: This product contains chemicals known to the State of California to cause cancer.
<b>Titanium dioxide (13463-67-7)</b>	
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)	
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)	
U.S. - Idaho - Occupational Exposure Limits - TWAs	
U.S. - Illinois - Toxic Air Contaminant Carcinogens	
RTK - U.S. - Massachusetts - Right To Know List	
U.S. - Michigan - Occupational Exposure Limits - TWAs	
U.S. - Minnesota - Chemicals of High Concern	
U.S. - Minnesota - Hazardous Substance List	
U.S. - Minnesota - Permissible Exposure Limits - TWAs	
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour	
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual	

# Nissen High Temperature Metal Marker

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - New York - Occupational Exposure Limits - TWAs  
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour  
U.S. - Oregon - Permissible Exposure Limits - TWAs  
RTK - U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - Tennessee - Occupational Exposure Limits - TWAs  
U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term  
U.S. - Vermont - Permissible Exposure Limits - TWAs  
U.S. - Washington - Permissible Exposure Limits - STELs  
U.S. - Washington - Permissible Exposure Limits - TWAs

### **Carbon black (1333-86-4)**

U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)  
U.S. - Idaho - Occupational Exposure Limits - TWAs  
U.S. - Illinois - Toxic Air Contaminant Carcinogens  
U.S. - Illinois - Toxic Air Contaminants  
U.S. - Maine - Chemicals of High Concern  
RTK - U.S. - Massachusetts - Right To Know List  
U.S. - Michigan - Occupational Exposure Limits - TWAs  
U.S. - Minnesota - Chemicals of High Concern  
U.S. - Minnesota - Hazardous Substance List  
U.S. - Minnesota - Permissible Exposure Limits - TWAs  
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - New Jersey - Special Health Hazards Substances List  
U.S. - New York - Occupational Exposure Limits - TWAs  
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour  
U.S. - Oregon - Permissible Exposure Limits - TWAs  
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances  
RTK - U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - Tennessee - Occupational Exposure Limits - TWAs  
U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term  
U.S. - Vermont - Permissible Exposure Limits - TWAs  
U.S. - Washington - Permissible Exposure Limits - STELs  
U.S. - Washington - Permissible Exposure Limits - TWAs  
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet  
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet  
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater  
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

### **Stoddard solvent (8052-41-3)**

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)  
U.S. - Idaho - Occupational Exposure Limits - TWAs  
RTK - U.S. - Massachusetts - Right To Know List  
U.S. - Michigan - Occupational Exposure Limits - TWAs  
U.S. - Minnesota - Chemicals of High Concern  
U.S. - Minnesota - Hazardous Substance List

# Nissen High Temperature Metal Marker

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Minnesota - Permissible Exposure Limits - TWAs  
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour  
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual  
 RTK - U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - New York - Occupational Exposure Limits - TWAs  
 U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour  
 U.S. - Oregon - Permissible Exposure Limits - TWAs  
 U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups  
 RTK - U.S. - Pennsylvania - RTK (Right to Know) List  
 U.S. - Tennessee - Occupational Exposure Limits - TWAs  
 U.S. - Texas - Effects Screening Levels - Long Term  
 U.S. - Texas - Effects Screening Levels - Short Term  
 U.S. - Vermont - Permissible Exposure Limits - TWAs  
 U.S. - Washington - Permissible Exposure Limits - STELs  
 U.S. - Washington - Permissible Exposure Limits - TWAs  
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet  
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet  
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater  
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

### Petroleum distillates, hydrotreated light (64742-47-8)

U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour  
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual  
 U.S. - Texas - Effects Screening Levels - Long Term  
 U.S. - Texas - Effects Screening Levels - Short Term

### Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with montmorillonite ((Al<sub>1.33</sub>-1.67Mg<sub>0.33</sub>-0.67)(Ca<sub>0</sub>-1Na<sub>0</sub>-1)0.33Si<sub>4</sub>(OH)<sub>2</sub>O<sub>10</sub>.xH<sub>2</sub>O)) (68911-87-5)

U.S. - Texas - Effects Screening Levels - Long Term  
 U.S. - Texas - Effects Screening Levels - Short Term

## Canadian Regulations

### Nissen High Temperature Metal Marker

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--



### Titanium dioxide (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
----------------------	--

### Carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Listed on the Canadian Ingredient Disclosure List

IDL Concentration 1 %

WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
----------------------	--

### Stoddard solvent (8052-41-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Listed on the Canadian Ingredient Disclosure List

IDL Concentration 1 %

WHMIS Classification	Class B Division 3 - Combustible Liquid
----------------------	---

# Nissen High Temperature Metal Marker

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
--	---

### Petroleum distillates, hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

### Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with montmorillonite ((Al1.33-1.67Mg0.33-0.67)(Ca0-1Na0-1)0.33Si4(OH)2O10.xH2O)) (68911-87-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
----------------------	---

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision date** : 07/28/2014

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.


### GHS Full Text Phrases:

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1B	Carcinogenicity Category 1B
Carc. 2	Carcinogenicity Category 2
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Muta. 1B	Germ cell mutagenicity Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

**NFPA Health Hazard** : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

**NFPA Fire Hazard** : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

**NFPA Reactivity** : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



# Nissen High Temperature Metal Marker

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

### Party Responsible for the Preparation of This Document

J.P. Nissen Co.  
2544 Fairhill Avenue  
Glenside, PA 19038  
215-886-2025

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

North America GHS US 2012 & WHMIS