

#### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: **Coated Abrasive** SDS Manufacturer Number: 1047337\_CA\_All

Manufacturer Name: Saint-Gobain Abrasives, Inc.

1 New Bond Street Address: Worcester, MA 01615

Website: www.Nortonabrasives.com

General Phone Number: 508-795-5000 Emergency Phone Number: 508-795-5000



| HMIS                   |   |
|------------------------|---|
| Health Hazard          | 1 |
| Fire Hazard            | 0 |
| Reactivity             | 0 |
| Personal<br>Protection | x |

#### SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name               | CAS# Ingredient Percent |                    | EC Num.   |  |
|-----------------------------|-------------------------|--------------------|-----------|--|
| Aluminum Oxide, Non-fibrous | 1344-28-1               | 60 - 100 by weight | 215-691-6 |  |
| Paper - Processed Cellulose | 9004-34-6               | 1 - 5 by weight    | 232-674-9 |  |

## SECTION 3: HAZARDS IDENTIFICATION

Potential Health Effects:

Ingestion:

Eye: Dust may cause slight irritation.

Skin: Dust from this product may cause temporary mechanical irritation.

Inhalation: Dusts from this product may cause mechanical irritation of the nose, throat and respiratory tract.

Ingestion:  $Ingestion\ of\ this\ product\ is\ unlikely.\ However,\ ingestion\ of\ product\ may\ produce\ gastrointestinal$ 

irritation and disturbances.

Chronic Health Effects: Chronic health effects are not expected as long as good hygiene and proper safety precautions are

#### SECTION 4: FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of

the eyes by separating the eyelids with fingers. Get medical attention, if irritation or symptoms of overexposure persists.

Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists. Skin Contact:

Inhalation: If dust from cutting or drilling is inhaled, remove the affected person to fresh air. If symptoms persist, get medical attention.

Accidental ingestion of this material is unlikely. If this does occur, watch person for several days to make sure intestinal blockage does not occur. If symptoms persist, call a physician.

Note to Physicians: No information available.

## SECTION 5 : FIRE FIGHTING MEASURES

Flammable Properties: Non Flammable. Flash Point: Does not apply. Auto Ignition Temperature: Not determined. Lower Flammable/Explosive Limit: Not available.

Upper Flammable/Explosive Limit: Not available.

Extinguishing Media: Use any extinguishing media appropriate for the surrounding fires.

Unsuitable Media:

Protective Equipment: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or

equivalent) and full protective gear.

NFPA Ratings:

NFPA Health: 1 NFPA Flammability: 0 NFPA Reactivity: 1

NFPA Other:

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

Containment of this material should not be necessary. Methods for containment:

Shovel or sweep up for re-use or disposal. Avoid creating dusty conditions. Evaluate residue to determine if it is a hazardous waste by characteristic. Methods for cleanup:

Dispose of in accordance with Local, State, Federal and Provincial regulations.

#### SECTION 7: HANDLING and STORAGE

Handling: Handle with adequate ventilation for nuisance dust.

No special storage conditions required. Storage:

Hygiene Practices: Wear suitable gloves and eye/face protection.

# SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

**Engineering Controls:** General dilution ventilation and/or local exhaust ventilation should be provided as necessary to

maintain exposures below occupational exposure limits.

Eye/Face Protection: Always WEAR SAFETY GLASSES or some type of eye protection when grinding.

Skin Protection Description:

Protective gloves. Long sleeved shirt and long pants.

Respiratory Protection: When workers are facing airborne particulate/dust concentrations above the exposure limit they must

use appropriate certified respirators.
A properly fitted NIOSH approved disposable N 95 type dust respirator or better is recommended.

Use of this product may create elevated sound levels. Hearing protection should be worn where required (see OSHA 29 CFR 1910.134 and other applicable regulations). Other Protective:

Handle in accordance with good industrial hygiene and safety practice. General Hygiene Considerations:

Remove and wash contaminated clothing before re-use. Avoid getting dust into boots and gloves through wrist bands and pant tucks.

## EXPOSURE GUIDELINES

| Ingredient                      | Guideline OSHA  | Guideline NIOSH   | Guideline ACGIH   | Quebec Canada                                       | Ontario Canada                                       |
|---------------------------------|---|---|---|---|--|
| Aluminum Oxide, Non-<br>fibrous | PEL-TWA: 5 mg/m3<br>Respirable fraction (R)<br>PEL-TWA: 15 mg/m3<br>Total particulate/dust<br>(T) |   | TLV-TWA: 10 mg/m3   | VEMP-TWA: 10<br>mg/m3 Total<br>particulate/dust (T) | OEL-TWAEV: 10<br>mg/m3 Total<br>particulate/dust (T) |
| Paper - Processed<br>Cellulose  | PEL-TWA: 15 mg/m3<br>Total particulate/dust<br>(T)<br>PEL-TWA: 5 mg/m3<br>Respirable fraction (R) | REL-TWA: 10 mg/m3<br>Total particulate/dust<br>(T) REL-TWA: 5<br>mg/m3 Respirable<br>fraction (R) | TLV-TWA: 10 mg/m3   | VEMP-TWA: 10 ppm<br>Total particulate/dust<br>(T)   | OEL-TWAEV: 10<br>mg/m3 Total<br>particulate/dust (T) |
| Ingredient                      | Alberta Canada  | Mexico  | British Columbia<br>Canada  |   |  |
| Aluminum Oxide, Non-<br>fibrous | OEL-TWA: 10 mg/m3   | MPE-PPT: 0.1 mg/m3<br>Respirable fraction (R)   | OEL-TWA: 3 mg/m3<br>Respirable fraction (R)<br>OEL-TWA: 10 mg/m3<br>OEL-TWA: 10 mg/m3<br>Total particulate/dust<br>(T)<br>OEL-STEL: 20 mg/m3<br>Total particulate/dust<br>(T) |   |  |
| Paper - Processed<br>Cellulose  | OEL-TWA: 10 mg/m3   | LMPE-PPT: 10 mg/m3<br>LMPE-CT: 20 mg/m3   | OEL-TWA: 3 mg/m3<br>Respirable fraction (R)<br>OEL-TWA: 10 mg/m3<br>Total particulate/dust<br>(T)   |   |  |

## SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Solid article. Odor: Odorless. Flash Point: Does not apply. Auto Ignition Temperature: Not determined.

#### SECTION 10: STABILITY and REACTIVITY

Chemical Stability: Stable under normal conditions.

Hazardous Polymerization: Hazardous polymerization does not occur. Conditions to Avoid: Keep away from heat, sparks, or open flame.

In use, dust and decomposing odors may be generated. In most cases, the material removed from the workplace will be significantly greater than the sandpaper components. Coolants may produce other decomposition products. Special Decomposition Products:

Thermal decomposition may produce trace amounts of ammonia and formaldehyde.

#### SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity: This product has not been tested for its toxicity.

<u>Aluminum Oxide, Non-fibrous</u>:

BD1200000 RTECS Number:

Inhalation - Rat TCLo: 200 mg/m3/5H/28W (Intermittent) [Lungs, Thorax, or Respiration - Structural or functional change in trachea or bronchi; Lungs, Thorax, or Respiration - Chronic pulmonary edema; Related to Chronic Data - death] (RTECS) Inhalation:

Paper - Processed Cellulose:

RTECS Number: FJ5691460

Inhalation: Inhalation - Rat LC50: >5800 mg/m3/4H [Details of toxic effects not reported other than lethal dose

value] (RTECS)

Ingestion: Oral - Rat LD50: >5 gm/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

#### SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product

## SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal: Use standard landfill methods consistent with applicable Federal, State, Provincial and local laws.

#### SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Not regulated as hazardous material for transportation.

DOT UN Number: Not regulated as hazardous material for transportation.

IATA Shipping Name: Not regulated as hazardous material for transportation.

Canadian Shipping Name: This product is Not Regulated under the Transportation of Dangerous Goods Act. (CAN).

#### SECTION 15: REGULATORY INFORMATION

# **Inventory Status**

|                             | EINECS Number | Canada DSL | TSCA Inventory |  |
|-----------------------------|---------------|------------|----------------|--|
|                             |               |            | Status         |  |
| Aluminum Oxide, Non-fibrous |               | Listed     | Listed         |  |
| Paper - Processed Cellulose | 232-674-9     | Listed     | Listed         |  |

## Aluminum Oxide, Non-fibrous:

Canada IDL: Identified under the Canadian Hazardous Products Act Ingredient Disclosure List: 0.1%.50(1298)

Aluminum Oxide, Non-fibrous:

EC Number: 215-691-6

Paper - Processed Cellulose:

EC Number: 232-674-9

## State Right To Know

|                             | PA     | MA     | ц   |  |
|-----------------------------|--------|--------|---|--|
| Aluminum Oxide, Non-fibrous | Listed | Listed | Listed: NJ Hazardous<br>List; Substance<br>Number: 2891 |  |
| Paper - Processed Cellulose | Listed | Listed |   |  |

# SECTION 16: ADDITIONAL INFORMATION

HMIS Ratings:

HMIS Health Hazard: 1
HMIS Fire Hazard: 0
HMIS Reactivity: 0
HMIS Personal Protection: X

SDS Creation Date: August 15, 2009
SDS Revision Date: July 01, 2013

Copyright© 1996-2015 Actio Corporation. All Rights Reserved.