# SAINT-GOBAIN

## SAFETY DATA SHEET

#### SECTION 1 : IDENTIFICATION

Product identifier used on the label:	
Product Name:	Coated Abrasive

Other means of identification:

Recommended use of the chemical and restrictions on use:

Chemical manufacturer address and teleph	none number:
Manufacturer Name:	Saint-Gobain Abrasives, Inc.
Address:	1 New Bond Street Worcester, MA 01615
Website:	www.Nortonabrasives.com
General Phone Number:	508-795-5000
Emergency phone number:	
Emergency Phone Number:	508-795-5000

### SECTION 2 : HAZARD(S) IDENTIFICATION

<u>Classification of the chemical in accordance with CFR 1910.1200(d)(f):</u>

 $\underline{ \text{Hazards not otherwise classified that have been identified during the classification process:}$ 

Potential Health Effects:	
Eye:	Dust may cause slight irritation.
Skin:	Dust from this product may cause temporary mechanical irritation.
Inhalation:	Dusts from this product may cause mechanical irritation of the nose, throat and respiratory tract.
Ingestion:	Ingestion of this product is unlikely. However, ingestion of product may produce gastrointestinal irritation and disturbances.
Chronic Health Effects:	Chronic health effects are not expected as long as good hygiene and proper safety precautions are practiced.

#### Phenol formaldehyde polymer

Chronic Health Effects:

Dust generated from intended use may contain trace amounts of phenol and formaldehyde which under excessive exposure may cause skin sensitization and airway obstruction.

#### SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

<u>Mixtures:</u>			
Chemical Name	CAS#	Ingredient Percent	EC Num.
Calcium Silicate	13983-17-0	5 - 10 by weight	237-772-5
Inorganic fluorides	Not Applicable	5 - 10 by weight	
Aluminum Oxide, Non-fibrous	1344-28-1	30 - 60 by weight	215-691-6
Phenol formaldehyde polymer	9003-35-4	10 - 30 by weight	
Paper - Processed Cellulose	9004-34-6	30 - 60 by weight	232-674-9

SECTION 4 : FIRST AID MEASURES

<u>,,</u>	<u>-</u>
Eye Contact:	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get medical attention, if irritation or symptoms of overexposure persists.
Skin Contact:	Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
Inhalation:	If dust from cutting or drilling is inhaled, remove the affected person to fresh air. If symptoms persist, get medical attention.
Ingestion:	Accidental ingestion of this material is unlikely. If this does occur, watch person for several days to make sure intestinal blockage does not occur. If symptoms persist, call a physician.
Indication of immediate medical at	tention and special treatment needed:

Note to Physicians: No information available.

## SECTION 5 : FIRE FIGHTING MEASURES

Suitable Extinguishing Media:	Use any extinguishing media appropriate for the surrounding fires.
Unsuitable extinguishing media:	None.
Special protective equipment and	precautions for fire-fighters:
	precautions for fire-fighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Protective Equipment:	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved o
Protective Equipment:	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved o
<u>Special protective equipment and j</u> Protective Equipment: <u>NFPA Ratings:</u> NFPA Health: NFPA Flammability:	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved on equivalent) and full protective gear.

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

NFPA Other:

Methods and materials for conta	ainment and cleaning up:
Methods for containment:	Containment of this material should not be necessary.
Methods for cleanup:	Shovel or sweep up for re-use or disposal. Avoid creating dusty conditions. Evaluate residue to determine if it is a hazardous waste by characteristic. Dispose of in accordance with Local, State, Federal and Provincial regulations.

## SECTION 7 : HANDLING and STORAGE

Precautions for safe handling:	
Handling:	Handle with adequate ventilation for nuisance dust.
Hygiene Practices:	Wear suitable gloves and eye/face protection.
Conditions for safe storage, including	ng any incompatibilities:
Storage:	No special storage conditions required.

### SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE GUIDELINES:

Ingredient	Guideline OSHA	Guideline NIOSH	Guideline ACGIH	Quebec Canada	Ontario Canada
Calcium Silicate	PEL-TWA: 15 mg/m3 Total particulate/dust (T) PEL-TWA: 5 mg/m3 Respirable fraction (R)		TLV-TWA: 10 mg/m3 Inhalable fraction (I) TLV-TWA: 3 mg/m3 Respirable fraction (R)	VEMP-TWA: 10 mg/m3 Total particulate/dust (T) VEMP-TWA: 5 mg/m3 Respirable fraction (R)	
Inorganic fluorides	PEL-TWA 2.5 mg/m3	REL-TWA 2.5 mg/m3	TLV-TWA 2.5 mg/m3		
Aluminum Oxide, Non- fibrous	PEL-TWA: 5 mg/m3 Respirable fraction (R) PEL-TWA: 15 mg/m3 Total particulate/dust (T)		TLV-TWA: 10 mg/m3	VEMP-TWA: 10 mg/m3 Total particulate/dust (T)	OEL-TWAEV: 10 mg/m3 Total particulate/dust (T)
Paper - Processed Cellulose	PEL-TWA: 15 mg/m3 Total particulate/dust (T) PEL-TWA: 5 mg/m3 Respirable fraction (R)	REL-TWA: 10 mg/m3 Total particulate/dust (T) REL-TWA: 5 mg/m3 Respirable fraction (R)	TLV-TWA: 10 mg/m3	VEMP-TWA: 10 ppm Total particulate/dust (T)	OEL-TWAEV: 10 mg/m3 Total particulate/dust (T)
Ingredient	Alberta Canada	Mexico	British Columbia Canada		
Aluminum Oxide, Non-	OEL-TWA: 10 mg/m3	MPE-PPT: 0.1 mg/m3	OEL-TWA: 3 mg/m3		

fibrous		Respirable fraction (R)	Respirable fraction (R) OEL-TWA: 10 mg/m3 OEL-TWA: 10 mg/m3 Total particulate/dust (T) OEL-STEL: 20 mg/m3 Total particulate/dust (T)	
Paper - Processed Cellulose	OEL-TWA: 10 mg/m3		OEL-TWA: 3 mg/m3 Respirable fraction (R) OEL-TWA: 10 mg/m3 Total particulate/dust (T)	

### Appropriate engineering controls:

Engineering Controls:	General dilution ventilation and/or local exhaust ventilation should be provided as necessary to maintain exposures below occupational exposure limits.
Individual protection measures:	
Eye/Face Protection:	Always WEAR SAFETY GLASSES or some type of eye protection when grinding.
Skin Protection Description:	Protective gloves. Long sleeved shirt and long pants.
Respiratory Protection:	When workers are facing airborne particulate/dust concentrations above the exposure limit they must use appropriate certified respirators. A properly fitted NIOSH approved disposable N 95 type dust respirator or better is recommended.
Other Protective:	Use of this product may create elevated sound levels. Hearing protection should be worn where required (see OSHA 29 CFR 1910.134 and other applicable regulations).
General Hygiene Considerations:	Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Avoid getting dust into boots and gloves through wrist bands and pant tucks.

## SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL AND CHEMICAL PROPERTIES:		
Physical State Appearance:	Solid article.	
Odor:	Odorless.	
Flash Point:	Does not apply.	
Lower Flammable/Explosive Limit:	Not available.	
Upper Flammable/Explosive Limit:	Not available.	
Auto Ignition Temperature:	Not determined.	

## SECTION 10 : STABILITY and REACTIVITY

Chemical Stability:	
Chemical Stability:	Stable under normal conditions.
Possibility of hazardous reactions:	
Hazardous Polymerization:	Hazardous polymerization does not occur.
Conditions To Avoid:	
Conditions to Avoid:	Keep away from heat, sparks, or open flame.
Hazardous Decomposition Products	<u></u>
Special Decomposition Products:	In use, dust and decomposing odors may be generated. In most cases, the material removed from the workplace will be significantly greater than the sandpaper components. Coolants may produce other decomposition products. Thermal decomposition may produce trace amounts of ammonia and formaldehyde.

## SECTION 11 : TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:		
Acute Toxicity:	This product has not been tested for its toxicity.	
Calcium Silicate :		
RTECS Number:	ZC9750000	
Aluminum Oxide, Non-fibrous :		
RTECS Number:	BD1200000	
Inhalation:	Inhalation - Rat TCLo: 200 mg/m3/5H/28W (Intermittent) [Lungs, Thorax, or Respiration - Structural or functional change in trachea or bronchi; Lungs, Thorax, or Respiration - Chronic pulmonary edema; Related to Chronic Data - death] (RTECS)	
Phenol formaldehyde polymer :		
RTECS Number:	SM8542500	
Skin:	Administration onto the skin - Rat LD50 : >2 gm/kg [Details of toxic effects not reported other than lethal dose value ] (RTECS)	
Coated Abra Revision: 07/0		

Ingestion:	Oral - Rat LD50 : >5 gm/kg [Details of toxic effects not reported other than lethal dose value ] (RTECS)	
Paper - Processed Cellulose :		
RTECS Number:	FJ5691460	
Inhalation:	Inhalation - Rat LC50: >5800 mg/m3/4H [Details of toxic effects not reported other than lethal dose value] (RTECS)	
Ingestion:	Oral - Rat LD50: >5 gm/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)	

#### SECTION 12 : ECOLOGICAL INFORMATION

#### Ecotoxicity:

Ecotoxicity:

No ecotoxicity data was found for the product.

### SECTION 13 : DISPOSAL CONSIDERATIONS

#### Description of waste:

Waste Disposal:

Use standard landfill methods consistent with applicable Federal, State, Provincial and local laws.

#### SECTION 14 : TRANSPORT INFORMATION

DOT Shipping Name:	Not regulated as hazardous material for transportation.
DOT UN Number:	Not regulated as hazardous material for transportation.
IATA Shipping Name:	Not regulated as hazardous material for transportation.
Canadian Shipping Name:	This product is Not Regulated under the Transportation of Dangerous Goods Act. (CAN).

## SECTION 15 : REGULATORY INFORMATION

 $\underline{Safety,\ health\ and\ environmental\ regulations\ specific\ for\ the\ product:}$ 

#### **Inventory Status**

	EINECS Number	Canada DSL	TSCA Inventory	
			Status	
Aluminum Oxide, Non-fibrous		Listed	Listed	
Phenol formaldehyde polymer		Listed	Listed	
Paper - Processed Cellulose	232-674-9	Listed	Listed	

#### Aluminum Oxide, Non-fibrous :

Canada IDL: Identified under the Canadian Hazardous Products Act Ingredient Disclosure List: 0.1%.50(1298)

Calcium Silicate :	
EC Number:	237-772-5
Aluminum Oxide, Non-fibrous:	
EC Number:	215-691-6
Paper - Processed Cellulose :	
EC Number:	232-674-9

### State Right To Know

	PA	MA	Ŋ	
Aluminum Oxide, Non-fibrous	Listed	Listed	Listed: NJ Hazardous List; Substance Number: 2891	
Paper - Processed Cellulose	Listed	Listed		

SECTION 16 : ADDITIONAL	L INFORMATION			
HMIS Ratings:				
HMIS Health Hazard:	1		Health Hazard	1
HMIS Fire Hazard:	0		Fire Hazard	0
HMIS Reactivity:	0		Reactivity	0
Coated Abrasive Revision: 07/01/2013		UPC Number: 66261086328 CA_AI		

SDS	Creation	Date:
SDS	Revision	Date:

December 15, 2010 July 01, 2013

Х

 ${\tt Copyright} \circledast$  1996-2015 Actio Corporation. All Rights Reserved.