

## SAFETY DATA SHEET

MAY BE USED TO COMPLY WITH OSHA'S HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200 AND SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) OF 1986 PUBLIC LAW 99-499. STANDARD SHOULD BE CONSULTED FOR SPECIFIC REQUIREMENTS.

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**NAME OF PRODUCT:** EUTECROD 16  
**SYNONYMS:** Eutectic 16  
**PRODUCT CODES:** 16-15-5K, 16-24-4.54K, 16-3246-5K

**MANUFACTURER/  
SUPPLIER:** EUTECTIC CORPORATION  
N94 W14355 GARWIN MACE DRIVE  
MENOMONEE FALLS, WI 53051 USA

**TELEPHONE NUMBER** (262) 532-4677  
**FAX NUMBER:** (262) 255-5542  
**EUTECTIC WEBSITE:** [www.eutectic.com](http://www.eutectic.com)

**PRODUCT USE:** Brazing Alloy

### SECTION 2: HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW:** Chemically stable and inert. Does not pose a fire hazard as shipped. **Non-Flammable:** Flames used for brazing can ignite combustibles. Refer to American National Standard Z49.1 for fire prevention during welding. These products as shipped are non-hazardous, nonflammable, non-explosive, and non-reactive. In case of fire, Use NIOSH/MSHA self contained breathing apparatus.

**ROUTES OF ENTRY:** Primary route of entry is the respiratory system. Other possible routes are eyes and/or skin contact.

#### POTENTIAL HEALTH EFFECTS:

**EYES:** Inert foreign body hazard only.  
**SKIN:** Rashes/irritations due to drying of the skin and/or mechanical abrasion related to skin-to-clothing contact or skin-to-skin contact. Spatter and flames from brazing may cause burns.  
**INGESTION:** Danger of serious damage to health if swallowed.  
**INHALATION:** Danger of serious damage to health by prolonged exposure through inhalation.

**ACUTE HEALTH HAZARDS:** see Section 11

**CHRONIC HEALTH HAZARDS:** see Section 11

**WARNING:** This product contains or produces a chemical known to the State of California to cause birth defects (or other reproductive harm) and cancer. (California Health & Safety Code 25249.5 et seq.).

**WARNING:** avoid breathing welding fumes and gases; they may dangerous to your health. Always use adequate ventilation and use appropriate personal protection equipment.

#### CARCINOGENICITY

**NICKEL** - is listed as being carcinogenic to humans on **IARC** and **NTP** lists, and is listed by **NIOSH** as being a potential occupational carcinogen (with no further categorization).

**WELDING FUMES** (not otherwise specified) are considered to be carcinogenic defined with no further categorization by **NIOSH** and **IARC**.

Package Labeling:

Although this product does not require a hazard warning label in all countries, we recommend that the safety advice should be observed:

**Pictograms:** GHS07- GHS08



**Contains Nickel**

**R-Phrases:**

Limited evidence of carcinogenic effect

May cause sensitization by skin contact

Toxic: danger of serious damage to health by prolonged exposure through inhalation

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Brazing/welding fumes and vapors may cause metal fume fever (headache, dizziness, dryness, cough, nausea, and fever) and these symptoms may appear 4-12 hours after exposure

May cause irritation by prolonged inhalation of brazing/welding fumes.

**GHS:**

Hazard categories:

Respiratory/skin sensitization: Skin Sens: 1

Carcinogenicity: Carc. 2

Specific target organ toxicity – repeated exposure: STOT RE 1

May cause an allergic skin reaction.

Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure.

**Hazard Statements:**

H317 May cause an allergic skin reaction

H351 Suspected of causing cancer

H372 Causes damage to organs through prolonged or repeated exposure

**Precautionary Statements:**

P285 In case of inadequate ventilation wear respiratory protection

P314 Get medical advice if you do not feel well

P280 Wear protective gloves/protective clothing/eye protection/face protection

P202 Do not handle until all safety precautions have been read and understood

P260 Do not breathe dust/fume/gas/mist/vapors/spray

P501 Dispose of contents/container to waste treatment facility in accordance with local and national regulations

**SECTION 2 NOTES:** Before using this product, contact your doctor to determine if exposure to product or use of this product will aggravate your medical conditions. Spatter and flames from brazing may cause burns and start fires.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**IMPORTANT:** This section covers the materials from which these products are manufactured. Any of the chemicals or compounds subject to reporting under Title III, in Section 313, of the Superfund Amendments and Reauthorization Act (SARA) are marked by the symbol #.

<u>INGREDIENTS</u>	<u>CAS NUMBER</u>	<u>Exposure Limit (mg/m<sup>3</sup>)</u>		<u>Percent Ingredients (by weight)</u>
		<u>OSHA PEL</u>	<u>ACGIH-TLV</u>	
Copper #	7440-50-8	0.1 (as fume)	0.2 (as fume)	40 - 70
Zinc #	7440-66-6	5 (as fume)	5 (as fume)	30 - 60
Nickel #	7440-02-0	1	0.2	10 - 30

**CAS / EINECS NUMBER / HAZARD CLASSIFICATION FOR ABOVE INGREDIENTS**

<u>INGREDIENTS</u>	<u>CAS NUMBER</u>	<u>EINECS NUMBER</u>	<u>Hazard Classification per ECD 67/548/EEC</u>
Copper #	7440-50-8	231-159-6	No
Zinc #	7440-66-6	231-175-3	no (Zn in solid article form)
Nickel #	7440-02-0	231-111-4	Carc. Cat. 3; R40 - T; R48/23 - R43

**SECTION 3 NOTES:** Exposure limits are subject to change. Contact ACGIH and OSHA for current values. See Section 16 for European Council Directive 67/548/EEC R-phrases and S-phrases

**SECTION 4: FIRST AID MEASURES**

**EMERGENCY & FIRST AID PROCEDURES:** Call for medical aid and inform them of the ingredients from Section 3. Employ first aid techniques recommended by The American Red Cross.

**EYES:** Flush with a large amount of fresh water for at least 15 minutes. Get medical attention.

**SKIN:** Wash affected area with soap and water to remove dust or particles. If rash develops, see a physician. Get medical attention for irritations that persist.

**INGESTION:** Seek medical attention immediately.

**INHALATION:** Remove to fresh air. If breathing is difficult administer oxygen. If breathing has stopped, begin artificial respiration and obtain medical assistance immediately.

**GENERAL:** Move to fresh air and call for medical aid.

**SECTION 4 NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:** See Section 3 for ingredients.

**SECTION 5: FIRE FIGHTING MEASURES**

**Non-Flammable** These products as shipped are non-hazardous, nonflammable, non-explosive, and non-reactive. In case of fire, use NIOSH/MSHA self contained breathing apparatus.

**NFPA HAZARD CLASSIFICATION:**

Health: 2                      Flammability: 0                      Reactivity: 0

Other: In case of fire, Use NIOSH/MSHA self contained breathing apparatus.

**HMIS HAZARD CLASSIFICATION:**

Health: 2                      Flammability: 0                      Reactivity: 0

Protection: In case of fire, Use NIOSH/MSHA self contained breathing apparatus.

**EXTINGUISHING MEDIA:** water, dry chemical extinguisher, CO<sub>2</sub> and use the extinguishing media recommended for the burning material and fire situation.

**SPECIAL FIRE FIGHTING PROCEDURES:** Low pressure extinguisher. In case of fire, Use NIOSH/MSHA self contained breathing apparatus.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** None

**HAZARDOUS DECOMPOSITION PRODUCTS:** Thermal decomposition may produce smoke and fumes of: ZnO (zinc) and CuO (copper).

**SECTION 5 NOTES:** None

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**ACCIDENTAL RELEASE MEASURES:** Shovel into a suitable container for proper disposal.

**PERSONAL PRECAUTIONS:** Breathing apparatus (particle filter) if a dust is formed.

**ENVIRONMENTAL PRECAUTIONS:** See section 12 and 13

**SECTION 6 NOTES:** None

**SECTION 7: HANDLING AND STORAGE**

**HANDLING:** Avoid exposure to dust, do not ingest and avoid contact with eyes. Some individuals can develop an allergic reaction to certain materials. Do not breathe dust. Do not eat, drink, or smoke when using this product. Wash thoroughly after using this product.

**STORAGE:** Keep material sealed and dry before use. After using, keep remaining product sealed and dry in original (labeled) packaging.

**SECTION 7 NOTES:** none

**SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION**



**Read and understand the manufacturer's instructions and precautionary label on this product.**

**ENGINEERING CONTROLS:** Proper ventilation **must** be maintained.

**VENTILATION:** Use enough ventilation, local exhaust at the spray area, or both, to keep the fumes and gases below the TLV's in the workers breathing and the general area. Train the worker to keep his head out of the fumes. Monitor fume levels and do not exceed permissible exposure limits or values.

**RESPIRATORY PROTECTION:** Do NOT breathe fumes. Use respirable fume respirator or air supplied respirator when brazing in a confined space or where local exhaust or ventilation does not keep exposure below the TLV's.

**EYE PROTECTION:** Wear safety glasses with side shields, face shield, and/or goggles to protect against airborne dust.

**PROTECTIVE CLOTHING:** Wear gloves when using or prolonged contact with skin or repeated contact with skin is likely. Wear hand and body protection to prevent injury. See ANSI Z49.1.

**SKIN PROTECTION:** Individuals having sensitive skin may find it beneficial to use a barrier cream or moisturizer when excessive or prolonged contact with skin is likely.

**WORK HYGIENIC PRACTICES:** Professionally wash contaminated clothing before re-use. Food and drink should not be consumed or tobacco products used, nor cosmetics applied in area where metal exposures are possible.

**EXPOSURE GUIDELINES:** Use industrial hygiene monitoring equipment to ensure that exposure does not exceed applicable national exposure limits.

**OTHER PROTECTIVE EQUIPMENT:** Full protective equipment normally used in soldering / brazing operation so as to prevent any contact. Review operations to avoid contact with hazardous gas, liquid, or solid. See also:

29CFR 1910.132 - 29 CFR 1910.140 Personal Protective Equipment  
29 CFR 1910.251 - 29 CFR 1910.257 Welding, Cutting and Brazing

**EFFECTS OF OVEREXPOSURE** - brazing may create one or more of the following health hazards:

**FUMES AND GASES** can be dangerous to your health.

**PRIMARY ROUTES OF ENTRY** are the respiratory system. Other possible routes are eyes and/or skin contact.

**PREEXISTING** respiratory or allergic conditions may be aggravated in some individuals (i.e. asthma, emphysema).

Brazing fumes cannot be classified simply. The composition and quantity of both are dependent upon the metal being brazed, the process, procedure, and the rod used. Other conditions which also influence the composition and quantity of the fumes and gases to which workers may be exposed include: coatings on the metal being brazed (such as paint, plating, or galvanizing), the volume of the work area, the quality and the amount of ventilation, position of the worker's head with respect to the fume plume, as well as the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from cleaning and degreasing activities).

When the material is consumed, fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section 3. Fume and decomposition products, not the ingredients in the rod, are important. Decomposition products include those originating from the volatilization, reaction, or oxidation of materials in Section 3, plus those from the base metal and coating, etc., as noted above. These components are virtually always present as complex oxides and not as metals (Characterization of Arc Welding Fume: American Welding Society). Reasonably expected fume constituents of the fume could include: complex oxides of copper and nickel. The table below lists reasonably expected fumes that may be generated:

<u>SUBSTANCE</u>	<u>CAS NUMBER</u>	<u>Exposure Limit (mg/m<sup>3</sup>)</u>	
		<u>OSHA PEL</u>	<u>ACGIH-TLV</u>
Copper # (as Cu)	7440-50-8	0.1 (as fume)	0.2 (as fume)
Nickel Oxide #	1313-99-1	1 (as Ni)	0.2 (as Ni)

Gaseous reaction products may include carbon monoxide and carbon dioxide. Monitor fume levels.

**SECTION 8 NOTES:** None

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** solid rod, no odor.  
**Melting point:** > 1000°F (540°C)  
**Flash point:** n.a.

**pH-Value:** n.a.  
**Boiling point:** n.a.

**SECTION 9 NOTES:** None

## SECTION 10: STABILITY AND REACTIVITY

**GENERAL:** These items are only intended for brazing application.

**STABILITY:** Product is chemically stable and non-reactive.

**CONDITIONS TO AVOID:** Keep product away from heat and moisture.

**MATERIALS TO AVOID:** Non-reactive.

**HAZARDOUS POLYMERIZATION:** Will not occur.

**REACTIVITY:** None.

**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** Fumes can be dangerous to your health. See Section 11

**SECTION 10 NOTES:** In other countries the exposure limits listed in Section 3 may be different and the appropriate country standards should be used.

## SECTION 11: TOXICOLOGICAL INFORMATION

**Threshold Limit Value:** The **ACGIH** recommended general limit for welding fume NOS (not otherwise specified) is 5 mg/m<sup>3</sup>. The **ACGIH 1999** preface states: "The **TLV-TWA** should be used as guides in the control of health hazards and should not be used as firm lines between safe and dangerous concentrations." See Section 8 for specific fume constituents that may modify the **TLV**. Brazing/welding vapours and fumes from brazing/welding may cause metal fume fever. Symptoms can appear 4 to 12 hours after. (headache, dizziness, dryness, cough, nausea and fever).

**ACUTE TOXICITY: Very toxic by inhalation.**

**SHORT TERM (ACUTE) OVEREXPOSURE:** Copper and zinc fumes produce **METAL FUME FEVER** which may result in severe tracheobronchitis, pneumonitis, pulmonary edema (throat dryness, cough, headache, vomiting, chest pains, and chills). Typically metal fume fever begins four to twelve hours after sufficient exposure to freshly formed fumes. First symptoms are a metallic taste, dryness, and irritation of the throat. Cough and shortness of breath may occur along with a headache, fatigue, nausea, vomiting, diarrhea, and painful spasms of the limbs. **COPPER-** Individuals with Wilson's Disease are at increased risk of **COPPER** poisoning. Exposure to fumes may result in discomfort such as dizziness, nausea, or dryness or irritation of nose, throat, or eyes. **INHALATION** may cause respiratory tract and mucous membrane irritation. Symptoms include nasal discharge and nosebleeds, coughing, sore throat and labored breathing. Severe exposure may cause bronchospasm and pulmonary edema. Absorption may cause systemic poisoning similar to that which occurs with ingestion. Copper poisoning can result in hemolytic anemia and kidney, liver, and spleen damage. Excessive inhalation of zinc fumes may produce symptoms known as **ZINC SHAKES**; an acute self limiting condition without recognized complications. Symptoms usually disappear within 24 hours. Symptomatic treatment such as bed rest, possibly aspirin or aspirin-free pain reliever to afford relief from fever and chills. Severe and prolonged overexposure to zinc oxide may cause pulmonary edema and pneumonia. Fumes may cause respiratory tract and mucous membrane irritation. Symptoms include nasal discharge and nosebleeds, coughing, sore throat and labored breathing. Severe exposure may cause bronchospasm and pulmonary edema. Absorption may cause systemic poisoning similar to that which occurs with ingestion. **NICKEL, NICKEL OXIDE** - May cause metallic taste, nausea, tightness in chest, fever, and allergic reactions. Overexposure to fumes may result in discomfort such as dizziness, nausea, or dryness or irritation of nose, throat, or eyes.

**CHRONIC TOXICITY: LONG TERM (CHRONIC) OVEREXPOSURE** is believed by some investigators to affect pulmonary functions. Target organs are eyes, skin, and respiratory system. Excessive **ZINC** intake has been associated with copper deficiency anemia. Prolonged or excessive exposures may result in argyria, a permanent localized blue-grey discoloration of the eye, skin, or mucous membranes. Primary route of entry is the respiratory system. **NICKEL, NICKEL OXIDE** - Long term overexposure to nickel products may cause lung fibrosis or pneumoconiosis. Symptoms of over-exposure to copper fumes include irritation to the eyes, upper respiratory system, metal fume fever, chills, muscle aches, nausea, fever, dry throat, cough, lassitude (weakness, exhaustion), metallic or sweat taste, and discoloration of skin. **FUMES AND GASES** can be dangerous to your health. Primary route of entry is inhalation of fumes. Preexisting respiratory or allergic conditions may be aggravated in some individuals.

**COPPER** may damage the liver, kidney, spleen, pancreas, and brain. Copper poisoning can result in hemolytic anemia and kidney, liver, and spleen damage. Ingestion of large amounts may be fatal.

**SECTION 11 NOTES:** Avoid direct inhalation of fumes during heating and use. Monitor fume levels.

#### SECTION 12: ECOLOGICAL INFORMATION

**MATERIAL:** Welding consumables and materials can degrade into the components used to manufacture the product. Avoid exposure to conditions that could lead to accumulation in soils and groundwater.

**CONTAMINATED PACKAGING:** Empty containers should be taken for local recycling, recovery, or waste disposal. Metals may be recycled.

**SECTION 12 NOTES:** None.

#### SECTION 13: DISPOSAL CONSIDERATION

**WASTE DISPOSAL METHOD:** Dispose of any rod and waste residues in accordance with EPA or local regulations.

**SECTION 13 NOTES:** Review U.S. Federal Hazardous Waste Regulations §40 CFR261 to determine if this is hazardous in USA. Please be advised that state and local requirements, or other country requirements, for waste disposal may be more restrictive or otherwise different than U.S. Federal regulations. It is not possible to give this product a waste code number according to the European waste catalogue because only the intended use of the user consents the assignment of a specific code number.

#### SECTION 14: TRANSPORTATION INFORMATION

**DOMESTIC TRANSPORT REGULATIONS (USA):** DOT - not regulated.

**DOMESTIC TRANSPORT REGULATIONS (CANADA):** TDG - not regulated.

**DOMESTIC TRANSPORT REGULATIONS (MEXICO):** MEX - not regulated.

**INTERNATIONAL TRANSPORT REGULATIONS:**

ICAO – not regulated

IATA – not regulated

IMDG / IMO – not regulated

**OTHER AGENCIES:** No international regulations or restrictions are applicable.

**SECTION 14 NOTES:** Handle with care to avoid damaging the product. Do not remove product identification label or warning label.

#### SECTION 15: REGULATORY INFORMATION

**Read and understand the manufacturer's Safety Data Sheet before handling or disposing of this product.**

**U.S. EPA TSCA (TOXIC SUBSTANCE CONTROL ACT):** All constituents of these products are on the TSCA inventory list or are excluded from listing.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center and to our Local Emergency Planning Committee.

**EPCRA/SARA TITLE III 313 TOXIC CHEMICALS:**

The following metallic components are listed as SARA 313 "TOXIC CHEMICALS" and are potentially subject to annual SARA 313 reporting. See Section 3 if the ingredient is present and for percent.

<u>INGREDIENT NAME</u>	<u>CAS NUMBER</u>	<u>DISCLOSURE THRESHOLD</u>
Chromium & chromium compounds	7440-47-3	1.0 % de minimis concentration
Chromium VI	Not listed	0.1 % de minimis concentration
Barium compounds	Not listed	1.0 % de minimis concentration
Cobalt	7440-48-4	0.1 % de minimis concentration
Copper	7440-50-8	1.0 % de minimis concentration
Manganese	7439-96-5	1.0 % de minimis concentration
Nickel	7440-02-0	0.1 % de minimis concentration
Aluminum (fume or dust)	7429-90-5	1.0 % de minimis concentration
Silver	7440-22-4	1.0 % de minimis concentration

Additional advice on labeling:

As a finished article the product does not need to be labeled in accordance with EC-directives or respective national laws.

**SECTION 15 NOTES:** International rules may vary and the appropriate regulations should be followed as defined by the country where the product is used.

**SECTION 16: OTHER INFORMATION**

This Safety Data Sheet has been revised due to modifications to several paragraphs and/or new format.  
Prepared by Eutectic Corporation. USA.

**Read and understand the manufacturer's instructions and precautionary label on this product.**

See American National Standard Z49.1, Safety in Welding and Cutting, published by the "American Welding Society," 550 N.W. LeJeune Road, Miami, FL 33126 and OSHA Publication 2206 (29CFR 1910), U.S. Government Printing Office, Superintendent of Documents, P.O. Box 371954, Pittsburgh, PA 15250-7954 for more detail on safe use of product.

R-phrases

**Nickel**

R40 : Limited evidence of a carcinogenic effect.

R43 : May cause sensitization by skin contact.

R48/23 : Toxic: danger of serious damage to health by prolonged exposure through inhalation.

S-Phrases

**Nickel**

S2: Keep out of the reach of children.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).



**SUPPLEMENTAL INFORMATION – DEFINITIONS:**

IARC: International Agency for the Research on Cancer  
NIOSH: National Institute for Occupational Safety and Health  
OSHA: U.S. Occupational Safety and Health Administration  
ACGIH: American Conference of Governmental Industrial Hygienists  
CAS: Chemical Abstracts Service Registry Number  
EINECS: European Inventory of Existing Chemical Substances

PEL: Permissible Exposure Limit  
NTP: National Toxicology Program  
TLV: Threshold Limit Value  
ECD: European Council Directive  
GHS: Globally Harmonized System

The information in this SDS was obtained from sources we believe are reliable. However, this information is provided without any representation or warranty, expressed or implied, regarding accuracy or correctness. The conditions or methods of handling, storage, use, and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons we do not assume responsibility and expressly disclaim liability of loss, damage, or expense arising from it or any way connected with the handling, storage, use, or disposal of the product.