

SDS

GHS Safety Data Sheet

WELD MOLD COMPANY

Nickel Base, Nickel Alloy Electrodes

PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Nickel Base, Nickel Alloy Electrodes

Common Name: 4000, 4000A, 4000AC, 4000B, 4000BC, 4112, 4112C, 4132C, 4132C, 4135C, 4182C, 4187, 4190C, 4141,

4411, ENiCrMo-10

SDS Number: 15
Revision Date: 5/7/2015
Version: 1
Product Use: Welding

Supplier Details: WELD MOLD COMPANY

750 Rickett Road Brighton, MI 48116

 Emergency:
 810-229-9521

 Contact:
 Kelley Henrikson

 Phone:
 810-229-9521

 Fax:
 810-229-9580

Email: khenrikson@weldmold.com
Web: www.weldmold.com

HAZARDS IDENTIFICATION

Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS):

Health, Skin corrosion/irritation, 1

Health, Specific target organ toxicity - Single exposure, 3

Health, Carcinogenicity, 1

2

Health, Specific target organ toxicity - Repeated exposure, 2

GHS Label elements, including precautionary statements

GHS Signal Word: DANGER

GHS Hazard Pictograms:



GHS Hazard Statements:

H314 - Causes severe skin burns and eye damage

H335 - May cause respiratory irritation

H350 - May cause cancer

H373 - May cause damage to organs through prolonged or repeated exposure

CGA-HG11 - SYMPTOMS MAY BE DELAYED.

GHS Precautionary Statements:

P232 - Protect from moisture.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

CGA-PG27 - Read and follow the Safety Data Sheet (SOS) before use.

Hazards not otherwise classified (HNOC) or not covered by GHS

Route of Entry: Eyes; Skin

Target Organs: Throat; Nose, Respiratory system

SDS Number: 15 Page 1 of 5 Revision Date: 5/7/2015

Inhalation: Short term overexposure to welding fumes may result in discomfort such as: dizziness, nausea, or dryness

or irritation of the nose, throat, lungs, and/or eyes.

ACCUTE EFFECTS: Irritating to the nose, throat and respiratory tract.

SUBCHRONIC/CHRONIC TOXICITY

CHRONIC: Chronic overexposure to welding fumes can result in: Chronic respiratory problems, iron

build-up in the lungs, bone erosion, reduced pulmonary functions and nervous disorders.

Skin Contact: The bright light produced by the arc can burn skin and eyes

Eye Contact: Fumes may be moderately irritating to the eyes

3

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas#	<u> </u>	Chemical Name
7439-96-5 7440-47-3 7440-02-0 7439-98-7 7440-03-1 7439-89-6 7440-50-8 7440-32-6 7429-90-5 1317-65-3 13463-67-7 15096-52-3 1302-78-9 9004-32-4	0.25-9% 13-30.5% 29-92% 0.5-9% 1-4% 0.4-12% 0.5-30% 0.2-4% 0.2-1% 4-14% 3-14% 3-20% 0.5-2.5% 0.5-4%	Manganese compounds and fumes (as Mn) Chromium Nickel, metallic and alloys Molybdenum: soluble and insoluble compounds Niobium Iron Copper Titanium Aluminum Calcium carbonate Titanium dioxide Sodiumaluminum flouride (as F) Bentonite Cellulose, carboxymethyl ether, sodium salt
1312-76-1 1344-09-8	2-10% 0.5-10%	Silicic acid, potassium salt Silicic acid, sodium salt

EXPOSURE LIMITS

CHEMICAL NAME	OSHA PEL	ACGIH TLV
Manganese compounds	5 mg/m3	1 mg/m3
Chromium	1 mg/m3	0.5 mg/m3
Nickel Metal	1 mg/m3	1.5 mg/m3
Soluble compounds, as Mo	15 mg/m3	10 mg/m3
Copper	1 mg/m3	1 mg/m3
Aluminum	15 mg/m3	10 mg/m3
Calcium Carbonate (limestone)	15 mg/m3	2 mg/m3
Titanium dioxide	10 mg/m3 NL = Not Listed	10 mg/m3
Sodium Silicate	NL	NL

4 FIRST AID MEASURES

5

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention. Non-irritating.

FIRE FIGHTING MEASURES

Welding consumables are not flammable, however the welding arc and sparks will ignite other combustible materials. Do not weld in the presence of combustible materials.

6 ACCIDENTAL RELEASE MEASURES

GENERAL PROCEDURES: Prevent waste from contaminating the surrounding environment. Discard any product, residue, disposable container or liner in an environmentally acceptable manner, in full compliance with federal, provincial, and local regulations.

7 HANDLING AND STORAGE

Storage Requirements: Store in a dry area.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

PERSONAL PROTECTION

EYES AND FACE: S39 - Wear eye/face protection

RESPIRATORY: Use sufficient ventilation, local exhaust at the arc, or both to keep the fumes and gases below TLV's in the workers breathing zone. In confined spaces use respirable fume respirator or air-supplied respirator.

PROTECTIVE CLOTHING: The intensity of the arc and the sparks emitted from it can cause severe burns. All skin should be covered

9 PHYSICAL AND CHEMICAL PROPERTIES

Physical State: The welding consumable discussed herein is composed of a wire strip or solid wire rod with or without a flux based core or outer coating.

10 STABILITY AND REACTIVITY

Hazardous Decomposition:

The composition and quantity of welding fumes generated are dependent upon several variables including the base material, base material contaminants and/or coatings (paint, galvanized, etc.) welding process utilized. Other factors that will effect the quantity of fumes available for inhalation are the number of welding operators in a designated work area, the quality of ventilation, the position of the operator with respect to the fume plume, as well as the presence of contaminants in the atmosphere from other manufacturing operations. Reasonably expected fume constituents of this product would include: complex oxides of iron, manganese, silicon, chromium, nickel, molybdenum, calcium, magnesium, and titanium.

COMMENTS: No hazard exists until this product is used in welding.

11 TOXICOLOGICAL INFORMATION

REPRODUCTIVE TOXIN: Not known MUTAGENICITY: Not known

12 ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: No data available

13 DISPOSAL CONSIDERATIONS

Dispose of in accordance with federal, state and local regulations.

14 TRANSPORT INFORMATION

SPECIAL SHIPPING NOTES: Special shipping considerations for this product are limited to those necessary to prevent damaging the product.

REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Manganese compounds and fumes (as Mn) (7439-96-5) [0.25-9%] MASS, NJHS, OSHAWAC, PA, SARA313, TSCA, TXAIR

RQ(5000LBS), Chromium (7440-47-3) [13-30.5%] CERCLA, EPCRAWPC, HWRCRA, MASS, NJHS, NRC, OSHAWAC, PA, PRIPOL, SARA313, TOXICPOL, TSCA, TXAIR

RQ(100LBS), Nickel, metallic and alloys (7440-02-0) [29-92%] CERCLA, EPCRAWPC, MASS, NJHS, NRC, OSHAWAC, PA, PRIPOL, SARA313, TOXICPOL, TSCA

Molybdenum: soluble and insoluble compounds (7439-98-7) [0.5-9%] MASS, OSHAWAC, PA, TSCA, TXAIR

Niobium (7440-03-1) [1-4%] TSCA

Iron (7439-89-6) [0.4-12%] TSCA

RQ(5000LBS), Copper (7440-50-8) [0.5-30%] CERCLA, EPCRAWPC, MASS, NJHS, OSHAWAC, PA, PRIPOL, SARA313, TOXICPOL, TSCA, TXAIR

Titanium (7440-32-6) [0.2-4%] TSCA

Aluminum (7429-90-5) [0.2-1%] EPCRAWPC, MASS, NJHS, OSHAWAC, PA, SARA313, TSCA, TXAIR

Calcium carbonate (1317-65-3) [4-14%] MASS, OSHAWAC, PA, TSCA, TXAIR

Titanium dioxide (13463-67-7) [3-14%] MASS, OSHAWAC, PA, TSCA, TXAIR

Sodiumaluminum flouride (as F) (15096-52-3) [3-20%] TSCA

Bentonite (1302-78-9) [0.5-2.5%] TSCA

Cellulose, carboxymethyl ether, sodium salt (9004-32-4) [0.5-4%] TSCA

Silicic acid, potassium salt (1312-76-1) [2-10%] TSCA

Silicic acid, sodium salt (1344-09-8) [0.5-10%] TSCA

Regulatory CODE Descriptions

RQ = Reportable Quantity
MASS = MA Massachusetts Hazardous Substances List
NJHS = NJ Right-to-Know Hazardous Substances
OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
SARA313 = SARA 313 Title III Toxic Chemicals
TSCA = Toxic Substances Control Act
TXAIR = TX Air Contaminants with Health Effects Screening Level
CERCLA = Superfund clean up substance
EPCRAWPC = EPCRA Water Priority Chemicals
HWRCRA = RCRA Hazardous Wastes
NRC = Nationally Recognized Carcinogens
PRIPOL = Clean Water Act Priority Pollutants
TOXICPOL = Clean Water Act Toxic Pollutants

NFPA: Health = 2, Fire = 0, Reactivity = 0, Specific Hazard = n/a

HMIS III: Health = 2, Fire = 0, Physical Hazard = 0

HMIS PPE: D - Face Shield and Eye Protection, Gloves, Apron







REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

313 REPORTABLE INGREDIENTS: This product contains some or all of the following reportable ingredients; Copper, Chromium, Manganese and Nickel

TSCA (TOXIC SUBSTANCE CONTROL ACT)

"WARNING": This product contains the following chemical(s) known to the state of California to cause cancer: Nickel (metallic) CAS# 7440-02-0