



Die Rod Electrodes

1 PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Die Rod Electrodes
Common Name: 515, 525, 535, 540, 545, 555, 5550, 5551, 5552, 9325, 9335, 9340, 9345
SDS Number: 24
Revision Date: 5/29/2015
Version: 2
Product Use: Welding
Supplier Details: WELD MOLD COMPANY
750 Rickett Road
Brighton, MI 48116

Emergency: 810-229-9521
Contact: Kelley Henrikson
Phone: 810-229-9521
Fax: 810-229-9580
Email: khenrikson@weldmold.com
Web: www.weldmold.com

2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS):

Health, Skin corrosion/irritation, 1
Health, Specific target organ toxicity - Single exposure, 3
Health, Carcinogenicity, 1
Health, Specific target organ toxicity - Repeated exposure, 2

GHS Label elements, including precautionary statements

GHS Signal Word: DANGER

GHS Hazard Pictograms:



GHS Hazard Statements:

H314 - Causes severe skin burns and eye damage
H335 - May cause respiratory irritation
H350 - May cause cancer
H373 - May cause damage to organs through prolonged or repeated exposure
CGA-HG11 - SYMPTOMS MAY BE DELAYED.

GHS Precautionary Statements:

P232 - Protect from moisture.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
CGA-PG27 - Read and follow the Safety Data Sheet (SOS) before use.

Hazards not otherwise classified (HNOC) or not covered by GHS

Route of Entry: Eyes; Skin
Target Organs: Throat; Nose, Respiratory system

Inhalation: Short term overexposure to welding fumes may result in discomfort such as: dizziness, nausea, or dryness or irritation of the nose, throat, lungs, and/or eyes.
 ACCUTE EFFECTS: Irritating to the nose, throat and respiratory tract.
 SUBCHRONIC/CHRONIC TOXICITY
 CHRONIC: Chronic overexposure to welding fumes can result in: Chronic respiratory problems, iron build-up in the lungs, bone erosion, reduced pulmonary functions and nervous disorders.

Skin Contact: The bright light produced by the arc can burn skin and eyes

Eye Contact: Fumes may be moderately irritating to the eyes

3 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas#	%	Chemical Name
7439-98-7	0.15-4.2%	Molybdenum: soluble and insoluble compounds
1317-65-3	7-16%	Calcium carbonate (limestone)
7789-75-5	3-6%	Calcium fluoride (CaF ₂)
68476-25-5	0-1%	Feldspar-group minerals
6487-48-5	0-1%	Potassium oxalate monohydrate
9004-34-6	0-1.5%	Cellulose
1302-78-9	0-5%	Bentonite clay
6834-92-0	0-5%	Sodium silicate
1312-76-1	0-5%	Potassium silicate
7439-89-6	68-97%	Iron
13983-17-0	0-1%	wollastonite
12001-26-2	<0.3%	Mica
7440-48-4	0-9.2%	Cobalt
7429-90-5	<0.3%	Aluminum
1314-62-1	0-0.65%	Vanadium (as V ₂ O ₅), respirable dust and fume
7440-32-6	0-0.5%	Titanium
13463-67-7	0-1.5%	Titanium dioxide
14040-11-0	0-4%	Tungsten carbonyl (W(CO) ₆), (OC-6-11)-
16389-88-1	0-6%	Dolomite (CaMg(CO ₃) ₂)
1344-09-8	0-1.4%	Sodium silicate

EXPOSURE LIMITS

<u>CHEMICAL NAME</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Soluble compounds, as Mo	15 mg/m ³	10 mg/m ³
Calcium Carbonate (limestone)	15 mg/m ³	2 mg/m ³
Calcium Fluoride	2.5 mg/m ³ As F	2.5 mg/m ³
Feldspar	5 mg/m ³ TWA	5 mg/m ³ TWA
Potassium oxalate monohydrate	NL	NL
Cellulose	10 mg/m ³	10 mg/m ³
Bentonite clay	5 mg/m ³ (Dust)	5 mg/m ³
Sodium silicate	NL	NL
Potassium silicate	NL	NL
Wollastonite	NL	NL
Mica	3 mg/m ³	3 mg/m ³
Cobalt	.01 mg/m ³ TWA	.02 mg/m ³ TWA
Aluminum	15 mg/m ³	10 mg/m ³ NL
Vanadium	0.05 mg/m ³ TWA	1 mg/m ³ TWA
Titanium	10 mg/m ³ NL = Not Listed	10 mg/m ³
Titanium dioxide	10 mg/m ³ NL = Not Listed	10 mg/m ³

Tungsten	5 mg/m3 TWA, 10mg/m3 STEL	5 mg/m3 TWA, 10 mg/m3 STEL (inhalable)
Dolomite	NL	NL
Dolomite	NL	NL
Sodium Silicate	NL * NL = Not Listed	NL

4 FIRST AID MEASURES

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention. Non-irritating.

5 FIRE FIGHTING MEASURES

Welding consumables are not flammable, however the welding arc and sparks will ignite other combustible materials. Do not weld in the presence of combustible materials.

6 ACCIDENTAL RELEASE MEASURES

GENERAL PROCEDURES: Prevent waste from contaminating the surrounding environment. Discard any product, residue, disposable container or liner in an environmentally acceptable manner, in full compliance with federal, provincial, and local regulations.

7 HANDLING AND STORAGE

Storage Requirements: Store in a dry area.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

PERSONAL PROTECTION

EYES AND FACE: S39 - Wear eye/face protection

RESPIRATORY: Use sufficient ventilation, local exhaust at the arc, or both to keep the fumes and gases below TLV's in the workers breathing zone. In confined spaces use respirable fume respirator or air-supplied respirator.

PROTECTIVE CLOTHING: The intensity of the arc and the sparks emitted from it can cause severe burns. All skin should be covered

9 PHYSICAL AND CHEMICAL PROPERTIES

Physical State: The welding consumable discussed herein is composed of a wire strip or solid wire rod with or without a flux based core or outer coating.

10 STABILITY AND REACTIVITY

Hazardous Decomposition: The composition and quantity of welding fumes generated are dependent upon several variables including the base material, base material contaminants and/or coatings (paint, galvanized, etc.) welding process utilized. Other factors that will effect the quantity of fumes available for inhalation are the number of welding operators in a designated work area, the quality of ventilation, the position of the operator with respect to the fume plume, as well as the presence of contaminants in the atmosphere from other manufacturing operations. Reasonably expected fume constituents of this product would include: complex oxides of iron, manganese, silicon, chromium, nickel, molybdenum, calcium, magnesium, and titanium.

COMMENTS: No hazard exists until this product is used in welding.

11**TOXICOLOGICAL INFORMATION**

REPRODUCTIVE TOXIN: Not known
 MUTAGENICITY: Not known

12**ECOLOGICAL INFORMATION**

ENVIRONMENTAL DATA: No data available

13**DISPOSAL CONSIDERATIONS**

Dispose of in accordance with federal, state and local regulations.

14**TRANSPORT INFORMATION**

SPECIAL SHIPPING NOTES: Special shipping considerations for this product are limited to those necessary to prevent damaging the product.

15**REGULATORY INFORMATION**

Component (CAS#) [%] - CODES

 Molybdenum: soluble and insoluble compounds (7439-98-7) [0.15-4.2%] MASS, OSHAWAC, PA, TSCA, TXAIR

Calcium carbonate (limestone) (1317-65-3) [7-16%] MASS, OSHAWAC, PA, TSCA, TXAIR

Calcium fluoride (CaF₂) (7789-75-5) [3-6%] TSCA

Feldspar-group minerals (68476-25-5) [0-1%] TSCA

Potassium oxalate monohydrate (6487-48-5) [0-1%]

Cellulose (9004-34-6) [0-1.5%] MASS, OSHAWAC, PA, TSCA, TXAIR

Bentonite clay (1302-78-9) [0-5%] TSCA

Sodium silicate (6834-92-0) [0-5%] TSCA

Potassium silicate (1312-76-1) [0-5%] TSCA

Iron (7439-89-6) [68-97%] TSCA

Wollastonite (13983-17-0) [0-1%]

Cobalt (7440-48-4) [0-9.2%] MASS, NJHS, OSHAWAC, PA, PROP65, SARA313, TSCA, TXAIR

Titanium dioxide (13463-67-7) [0-1.5%] MASS, OSHAWAC, PA, TSCA, TXAIR

Tungsten carbonyl (W(CO)₆), (OC-6-11)- (14040-11-0) [0-4%] TSCA

Dolomite (CaMg(CO₃)₂) (16389-88-1) [0-6%] TSCA

Sodium Silicate (1344-09-8) [0-1.4%] TSCA

Regulatory CODE Descriptions

 RQ = Reportable Quantity
 MASS = MA Massachusetts Hazardous Substances List
 OSHAWAC = OSHA workplace Air Contaminants
 PA = PA Right-To-Know List of Hazardous Substances


TSCA = Toxic Substances Control Act
TXAIR = TX Air Contaminants with Health Effects Screening Level
NJHS = NJ Right-to-Know Hazardous Substances
PROP65 = CA Prop 65
SARA313 = SARA 313 Title III Toxic Chemicals

16 OTHER INFORMATION


NFPA: Health = 2, Fire = 0, Reactivity = 0, Specific Hazard = n/a

HMIS III: Health = 2, Fire = 0, Physical Hazard = 0

HMIS PPE: D - Face Shield and Eye Protection, Gloves, Apron



HMIS	
HEALTH	2
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	D



REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

313 REPORTABLE INGREDIENTS: This product contains some or all of the following reportable ingredients; Copper, Chromium, Manganese and Nickel

TSCA (TOXIC SUBSTANCE CONTROL ACT)

"WARNING": This product contains the following chemical(s) known to the state of California to cause cancer: Nickel (metallic) CAS# 7440-02-0