# **SAFETY DATA SHEET**



Nonflammable Gas Mixture: Argon 94.15-95% / Chlorine 5-5.85%

### **Section 1. Identification**

**GHS** product identifier

: Nonflammable Gas Mixture: Argon 94.15-95% / Chlorine 5-5.85%

Other means of identification

: Not available.

**Product type** 

: Gas.

**Product use** 

: Synthetic/Analytical chemistry.

SDS#

: 013316

Supplier's details

: Airgas USA, LLC and its affiliates 259 North Radnor-Chester Road

Suite 100

Radnor, PA 19087-5283

1-610-687-5253

24-hour telephone

: 1-866-734-3438

### Section 2. Hazards identification

**OSHA/HCS** status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: GASES UNDER PRESSURE - Compressed gas ACUTE TOXICITY (inhalation) - Category 4

SKIN CORROSION - Category 1 SERIOUS EYE DAMAGE - Category 1 AQUATIC HAZARD (ACUTE) - Category 2

#### **GHS** label elements

**Hazard pictograms** 







Signal word

: Danger

**Hazard statements** 

: Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation.

Harmful if inhaled.

Causes severe skin burns and eye damage.

Toxic to aquatic life.

#### **Precautionary statements**

**General** 

: Read and follow all Safety Data Sheets (SDS'S) before use. Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Close valve after each use and when empty. Use equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use a back flow preventative device in the piping. Use only equipment of compatible materials of construction.

**Prevention** 

: Wear protective gloves. Wear eye or face protection. Wear protective clothing. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Avoid breathing gas. Wash hands thoroughly after handling.

Response

: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.

Date of issue/Date of revision : 7/16/2018 Date of previous issue : No previous validation Version : 1 1/11

### Section 2. Hazards identification

**Storage Disposal** 

- : Store locked up. Protect from sunlight. Store in a well-ventilated place.
- : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified

In addition to any other important health or physical hazards, this product may displace oxygen and cause rapid suffocation.

# Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Other means of

identification

: Not available.

**Product code** : 013316

Ingredient name	%	CAS number
Argon	94.15 - 95	7440-37-1
chlorine	5 - 5.85	7782-50-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact** 

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Skin contact** 

Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: As this product is a gas, refer to the inhalation section.

#### Most important symptoms/effects, acute and delayed

### Potential acute health effects

**Eye contact** 

: Causes serious eye damage. Contact with rapidly expanding gas may cause burns or frostbite.

Inhalation

: Harmful if inhaled.

Skin contact

: Causes severe burns. Contact with rapidly expanding gas may cause burns or frostbite.

**Frostbite** Ingestion : Try to warm up the frozen tissues and seek medical attention.

: As this product is a gas, refer to the inhalation section.

#### Over-exposure signs/symptoms

Eye contact

: Adverse symptoms may include the following:, pain, watering, redness

Inhalation

: No specific data.

Date of issue/Date of revision 2/11 : 7/16/2018 Date of previous issue Version:1 : No previous validation

### Section 4. First aid measures

Skin contact

: Adverse symptoms may include the following:, pain or irritation, redness, blistering may occur

Ingestion

: Adverse symptoms may include the following:, stomach pains

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** 

**Protection of first-aiders** 

: No specific treatment.

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing media

**Unsuitable extinguishing** media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising

from the chemical

: Contains gas under pressure. In a fire or if heated, a pressure increase will occur and the container may burst or explode. This material is toxic to aquatic life. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal** decomposition products : Decomposition products may include the following materials: halogenated compounds

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not breathe gas. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

**Environmental precautions** 

: Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### Methods and materials for containment and cleaning up

Date of issue/Date of revision : 7/16/2018 Date of previous issue 3/11 Version: 1 : No previous validation

### Section 6. Accidental release measures

Small spill Large spill

- : Immediately contact emergency personnel. Stop leak if without risk.
- : Immediately contact emergency personnel. Stop leak if without risk. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### **Precautions for safe handling**

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Contains gas under pressure. Do not get in eyes or on skin or clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not puncture or incinerate container. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Use a suitable hand truck for cylinder movement.

Avoid release to the environment. Empty containers retain product residue and can be hazardous. Do not breathe gas.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52 °C (125 °F). Store locked up. Keep container tightly closed and sealed until ready for use. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

Ingredient name	Exposure limits
Argon	ACGIH TLV (United States, 3/2017). Oxygen
	Depletion [Asphyxiant].
chlorine	ACGIH TLV (United States, 3/2017).
	STEL: 2.9 mg/m³ 15 minutes.
	STEL: 1 ppm 15 minutes.
	TWA: 1.5 mg/m <sup>3</sup> 8 hours.
	TWA: 0.5 ppm 8 hours.
	NIOSH REL (United States, 10/2016).
	CEIL: 1.45 mg/m³ 15 minutes.
	CEIL: 0.5 ppm 15 minutes.
	OSHA PEL (United States, 6/2016).
	CEIL: 3 mg/m³
	CEIL: 1 ppm
	OSHA PEL 1989 (United States, 3/1989).
	STEL: 3 mg/m³ 15 minutes.
	STEL: 1 ppm 15 minutes.
	TWA: 1.5 mg/m <sup>3</sup> 8 hours.
	TWA: 0.5 ppm 8 hours.
	California PEL for Chemical Contaminants (
	Table AC-1) (United States).
	PEL: 0.5 ppm 8 hours.
	STEL: 1 ppm 15 minutes.

# Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Date of issue/Date of revision : 7/16/2018 Date of previous issue : No previous validation Version : 1 4/11

# Section 8. Exposure controls/personal protection

# **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

#### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

#### **Skin protection**

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

# Section 9. Physical and chemical properties

#### **Appearance**

Physical state : Gas.

Color : Not available.

Odor : Not available.

Odor threshold : Not available.

pH : Not available.

**Melting point** : -101°C (-149.8°F) This is based on data for the following ingredient: chlorine. Weighted

average: -184.08°C (-299.3°F)

Boiling point : Not available.

Critical temperature : Lowest known value: -122.4°C (-188.3°F) (Argon).

Flash point : Not available.

Evaporation rate : Not available.

Flammability (solid, gas) : Not available.

Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available.

**Vapor density** : Highest known value: 2.5 (Air = 1) (chlorine). Weighted average: 1.71 (Air = 1)

Gas Density (lb/ft 3) : Weighted average: 0.11

Date of issue/Date of revision : 7/16/2018 Date of previous issue : No previous validation Version : 1 5/11

## Section 9. Physical and chemical properties

Relative density : Not applicable.

Solubility : Not available.

Solubility in water : Not available.

Partition coefficient: n- : Not available.

octanol/water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Not applicable.

Flow time (ISO 2431) : Not available.

# Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

not be produced.

**Hazardous polymerization**: Under normal conditions of storage and use, hazardous polymerization will not occur.

# Section 11. Toxicological information

### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
chlorine	LC50 Inhalation Gas.	Rat	293 ppm	1 hours

### **Irritation/Corrosion**

Not available.

#### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

### Specific target organ toxicity (single exposure)

Not available.

Date of issue/Date of revision : 7/16/2018 Date of previous issue : No previous validation Version : 1 6/11

# **Section 11. Toxicological information**

### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Information on the likely routes of exposure

: Not available.

### Potential acute health effects

**Eye contact** : Causes serious eye damage. Contact with rapidly expanding gas may cause burns or

frostbite.

Inhalation : Harmful if inhaled.

**Skin contact**: Causes severe burns. Contact with rapidly expanding gas may cause burns or frostbite.

Ingestion : As this product is a gas, refer to the inhalation section.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:, pain, watering, redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:, pain or irritation, redness, blistering may

occur

Ingestion : Adverse symptoms may include the following:, stomach pains

#### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

#### Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

### **Acute toxicity estimates**

Not available.

Date of issue/Date of revision : 7/16/2018 Date of previous issue : No previous validation Version : 1 7/11

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
chlorine	Acute EC50 5.1 ppm Marine water	Algae - Macrocystis pyrifera - Young	4 days
	Acute LC50 2.03 μg/l Fresh water Acute LC50 30 μg/l Fresh water	Aquatic plants - Lemna minor Crustaceans - Asellus racovitzai Daphnia - Daphnia pulex Fish - Oncorhynchus mykiss	4 days 2 days 48 hours 96 hours

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Argon	0.74	-	low

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

# Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Empty Airgas-owned pressure vessels should be returned to Airgas. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

# Section 14. Transport information

	DOT	TDO		шъо	1474
	DOT	TDG	Mexico	IMDG	IATA
UN number	UN1956	UN1956	UN1956	UN1956	UN1956
UN proper shipping name	COMPRESSED GAS, N.O.S. (argon, chlorine)	COMPRESSED GAS, N.O.S. (argon, chlorine)	COMPRESSED GAS, N.O.S. (argon, chlorine )	COMPRESSED GAS, N.O.S. (argon, chlorine)	COMPRESSED GAS, N.O.S. (argon, chlorine)
Transport hazard class(es)	2.2	2.2	2.2	2.2	2.2
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.

<sup>&</sup>quot;Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the product."

Date of issue/Date of revision : 7/16/2018 Date of previous issue : No previous validation Version : 1 8/11

# Section 14. Transport information

**Additional information** 

**DOT Classification** : Reportable quantity 170.94 lbs / 77.607 kg. Package sizes shipped in quantities less

than the product reportable quantity are not subject to the RQ (reportable quantity)

transportation requirements.

**TDG Classification** : Product classified as per the following sections of the Transportation of Dangerous

Goods Regulations: 2.13-2.17 (Class 2).

**Explosive Limit and Limited Quantity Index** 0.125

Passenger Carrying Road or Rail Index 75

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according: Not available.

to Annex II of MARPOL and

the IBC Code

# Section 15. Regulatory information

U.S. Federal regulations : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

Clean Water Act (CWA) 311: chlorine

Clean Air Act (CAA) 112 regulated toxic substances: chlorine

Clean Air Act Section 112

(b) Hazardous Air

: Listed

**Pollutants (HAPs)** 

Clean Air Act Section 602

**Class I Substances** 

: Not listed

**Clean Air Act Section 602** 

**Class II Substances** 

: Not listed

**DEA List I Chemicals** 

(Precursor Chemicals)

: Not listed

**DEA List II Chemicals** 

: Not listed

(Essential Chemicals)

#### **SARA 302/304**

#### **Composition/information on ingredients**

			SARA 302 TPQ		SARA 304 RQ	
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
chlorine	5 - 5.85	Yes.	100	-	10	-

**SARA 304 RQ** : 170.9 lbs / 77.6 kg

**SARA 311/312** 

Classification : Refer to Section 2: Hazards Identification of this SDS for classification of substance.

**SARA 313** 

	Product name	CAS number	%
Form R - Reporting requirements	chlorine	7782-50-5	5 - 5.85
Supplier notification	chlorine	7782-50-5	5 - 5.85

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

#### **State regulations**

Date of issue/Date of revision 9/11 : 7/16/2018 Version: 1 Date of previous issue : No previous validation

## Section 15. Regulatory information

Massachusetts : The following components are listed: ARGON; CHLORINE

New York : The following components are listed: Chlorine

New Jersey : The following components are listed: ARGON; CHLORINE Pennsylvania : The following components are listed: ARGON; CHLORINE

**International regulations** 

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

#### **Inventory list**

Australia : All components are listed or exempted.

Canada : All components are listed or exempted.

China : All components are listed or exempted.

Europe : All components are listed or exempted.

Japan inventory (ENCS): Not determined.

Japan inventory (ISHL): Not determined.

Malaysia : Not determined.

New Zealand: All components are listed or exempted.Philippines: All components are listed or exempted.Republic of Korea: All components are listed or exempted.Taiwan: All components are listed or exempted.

Thailand : Not determined.

Turkey : Not determined.

United States : All components are listed or exempted.

Viet Nam : Not determined.

# Section 16. Other information

#### **Hazardous Material Information System (U.S.A.)**



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

**National Fire Protection Association (U.S.A.)** 

Date of issue/Date of revision : 7/16/2018 Date of previous issue : No previous validation Version : 1 10/11

### Section 16. Other information



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

#### Procedure used to derive the classification

Classification	Justification
GASES UNDER PRESSURE - Compressed gas ACUTE TOXICITY (inhalation) - Category 4 SKIN CORROSION - Category 1	On basis of test data Expert judgment Expert judgment
SERIOUS EYE DAMAGE - Category 1 AQUATIC HAZARD (ACUTE) - Category 2	Expert judgment Expert judgment

#### **History**

Date of printing : 7/16/2018

Date of issue/Date of : 7/16/2018

revision

Date of previous issue : No previous validation

Version : 1

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

**UN = United Nations** 

References : Not available.

#### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot quarantee that these are the only hazards that exist.

Date of issue/Date of revision : 7/16/2018 Date of previous issue : No previous validation Version : 1 11/11