

# SAFETY DATA SHEET

Flammable Liquid Mixture: 2-Methylpentane / 2,2-Dimethylbutane / 2,3-Dimethylbutane / 3-Methylpentane / Cyclopentane / Isopentane / N-Pentane

## Section 1. Identification

<b>GHS product identifier</b>	: Flammable Liquid Mixture: 2-Methylpentane / 2,2-Dimethylbutane / 2,3-Dimethylbutane / 3-Methylpentane / Cyclopentane / Isopentane / N-Pentane
<b>Other means of identification</b>	: Not available.
<b>Product use</b>	: Synthetic/Analytical chemistry.
<b>SDS #</b>	: 020478
<b>Supplier's details</b>	: Airgas USA, LLC and its affiliates 259 North Radnor-Chester Road Suite 100 Radnor, PA 19087-5283 1-610-687-5253
<b>24-hour telephone</b>	: 1-866-734-3438

## Section 2. Hazards identification

<b>OSHA/HCS status</b>	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
<b>Classification of the substance or mixture</b>	: FLAMMABLE LIQUIDS - Category 1 SKIN CORROSION/IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 AQUATIC HAZARD (LONG-TERM) - Category 2

### GHS label elements

#### **Hazard pictograms**



#### **Signal word**

#### **Hazard statements**

- : Danger
- : Extremely flammable liquid and vapor.  
May form explosive mixtures in Air.  
Causes skin irritation.  
May cause drowsiness and dizziness.  
Toxic to aquatic life with long lasting effects.

### Precautionary statements

#### **General**

- : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

#### **Prevention**

- : Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Avoid breathing vapor. Wash hands thoroughly after handling.

#### **Response**

- : Collect spillage. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention.

#### **Storage**

- : Store locked up. Store in a well-ventilated place. Keep cool.

#### **Disposal**

- : Dispose of contents and container in accordance with all local, regional, national and international regulations.

## Section 2. Hazards identification

**Hazards not otherwise classified** : None known.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture

**Other means of identification** : Not available.

### CAS number/other identifiers

**CAS number** : Not applicable.

**Product code** : 020478

Ingredient name	%	CAS number
isopentane	40 - 50	78-78-4
2,3-dimethylbutane	20 - 21	79-29-8
n-pentane	15 - 16	109-66-0
cyclopentane	14 - 15	287-92-3
2-methylpentane	7 - 8	107-83-5
3-methylpentane	0.5 - 0.9999	96-14-0
2,2-dimethylbutane	0.1 - 0.9999	75-83-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

**Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

**Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.

## Section 4. First aid measures

**Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness.

**Skin contact** : Causes skin irritation.

**Frostbite** : Try to warm up the frozen tissues and seek medical attention.

**Ingestion** : Can cause central nervous system (CNS) depression.

### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following; pain or irritation, watering, redness

**Inhalation** : Adverse symptoms may include the following; nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, unconsciousness

**Skin contact** : Adverse symptoms may include the following; irritation, redness

**Ingestion** : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

**Specific hazards arising from the chemical** : Extremely flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

## Section 6. Accidental release measures

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### Methods and materials for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

### Occupational exposure limits

## Section 8. Exposure controls/personal protection

isopentane

**ACGIH TLV (United States, 3/2016).**

TWA: 1000 ppm 8 hours.

**ACGIH TLV (United States, 3/2016).**STEL: 3500 mg/m<sup>3</sup> 15 minutes.

STEL: 1000 ppm 15 minutes.

TWA: 1760 mg/m<sup>3</sup> 8 hours.

TWA: 500 ppm 8 hours.

**NIOSH REL (United States, 10/2013).**CEIL: 1800 mg/m<sup>3</sup> 15 minutes.

CEIL: 510 ppm 15 minutes.

TWA: 350 mg/m<sup>3</sup> 10 hours.

TWA: 100 ppm 10 hours.

**OSHA PEL 1989 (United States, 3/1989).**STEL: 3600 mg/m<sup>3</sup> 15 minutes.

STEL: 1000 ppm 15 minutes.

TWA: 1800 mg/m<sup>3</sup> 8 hours.

TWA: 500 ppm 8 hours.

**ACGIH TLV (United States, 3/2016).**

TWA: 1000 ppm 8 hours.

**NIOSH REL (United States, 10/2013).**CEIL: 1800 mg/m<sup>3</sup> 15 minutes.

CEIL: 610 ppm 15 minutes.

TWA: 350 mg/m<sup>3</sup> 10 hours.

TWA: 120 ppm 10 hours.

**OSHA PEL (United States, 6/2016).**TWA: 2950 mg/m<sup>3</sup> 8 hours.

TWA: 1000 ppm 8 hours.

**OSHA PEL 1989 (United States, 3/1989).**STEL: 2250 mg/m<sup>3</sup> 15 minutes.

STEL: 750 ppm 15 minutes.

TWA: 1800 mg/m<sup>3</sup> 8 hours.

TWA: 600 ppm 8 hours.

**ACGIH TLV (United States, 3/2016).**TWA: 1720 mg/m<sup>3</sup> 8 hours.

TWA: 600 ppm 8 hours.

**NIOSH REL (United States, 10/2013).**TWA: 1720 mg/m<sup>3</sup> 10 hours.

TWA: 600 ppm 10 hours.

**OSHA PEL 1989 (United States, 3/1989).**TWA: 1720 mg/m<sup>3</sup> 8 hours.

TWA: 600 ppm 8 hours.

**ACGIH TLV (United States, 3/2016).**

TWA: 500 ppm 8 hours.

TWA: 1760 mg/m<sup>3</sup> 8 hours.

STEL: 1000 ppm 15 minutes.

STEL: 3500 mg/m<sup>3</sup> 15 minutes.**OSHA PEL 1989 (United States, 3/1989).**

TWA: 500 ppm 8 hours.

TWA: 1800 mg/m<sup>3</sup> 8 hours.

STEL: 1000 ppm 15 minutes.

STEL: 3600 mg/m<sup>3</sup> 15 minutes.**NIOSH REL (United States, 10/2013).**

TWA: 100 ppm 10 hours.

TWA: 350 mg/m<sup>3</sup> 10 hours.

CEIL: 510 ppm 15 minutes.

CEIL: 1800 mg/m<sup>3</sup> 15 minutes.**ACGIH TLV (United States, 3/2016).**

TWA: 500 ppm 8 hours.

TWA: 1760 mg/m<sup>3</sup> 8 hours.

STEL: 1000 ppm 15 minutes.

STEL: 3500 mg/m<sup>3</sup> 15 minutes.**OSHA PEL 1989 (United States, 3/1989).**

2-methylpentane

3-methylpentane

## Section 8. Exposure controls/personal protection

2,2-dimethylbutane

TWA: 500 ppm 8 hours.  
 TWA: 1800 mg/m<sup>3</sup> 8 hours.  
 STEL: 1000 ppm 15 minutes.  
 STEL: 3600 mg/m<sup>3</sup> 15 minutes.

### NIOSH REL (United States, 10/2013).

TWA: 100 ppm 10 hours.  
 TWA: 350 mg/m<sup>3</sup> 10 hours.  
 CEIL: 510 ppm 15 minutes.  
 CEIL: 1800 mg/m<sup>3</sup> 15 minutes.

### ACGIH TLV (United States, 3/2016).

TWA: 500 ppm 8 hours.  
 TWA: 1760 mg/m<sup>3</sup> 8 hours.  
 STEL: 1000 ppm 15 minutes.  
 STEL: 3500 mg/m<sup>3</sup> 15 minutes.

### OSHA PEL 1989 (United States, 3/1989).

TWA: 500 ppm 8 hours.  
 TWA: 1800 mg/m<sup>3</sup> 8 hours.  
 STEL: 1000 ppm 15 minutes.  
 STEL: 3600 mg/m<sup>3</sup> 15 minutes.

### NIOSH REL (United States, 10/2013).

TWA: 100 ppm 10 hours.  
 TWA: 350 mg/m<sup>3</sup> 10 hours.  
 CEIL: 510 ppm 15 minutes.  
 CEIL: 1800 mg/m<sup>3</sup> 15 minutes.

### Appropriate engineering controls

- Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Environmental exposure controls

- Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

- Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

- Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### Skin protection

#### Hand protection

- Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

#### Body protection

- Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

## Section 8. Exposure controls/personal protection

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## Section 9. Physical and chemical properties

### Appearance

**Physical state** : Liquid.

**Color** : Not available.

**Boiling/condensation point** : Lowest known value: 27.8°C (82°F) (Isopentane (2-Methylbutane)). Weighted average: 40.04°C (104.1°F)

**Melting/freezing point** : May start to solidify at the following temperature: -93.9°C (-137°F) This is based on data for the following ingredient: cyclopentane. Weighted average: -140.06°C (-220.1°F)

**Critical temperature** : Lowest known value: 187.25°C (369.1°F) (Isopentane (2-Methylbutane)).

**Odor** : Not available.

**Odor threshold** : Not available.

**pH** : Not available.

**Flash point** : Not available.

**Burning time** : Not applicable.

**Burning rate** : Not applicable.

**Evaporation rate** : Not available.

**Flammability (solid, gas)** : Not available.

**Lower and upper explosive (flammable) limits** : Not available.

**Vapor pressure** : Not available.

**Vapor density** : Highest known value: 3 (Air = 1) (2,3-dimethylbutane). Weighted average: 2.62 (Air = 1)

**Gas Density (lb/ft<sup>3</sup>)** : Weighted average: 0.28

**Relative density** : Not available.

**Solubility** : Not available.

**Solubility in water** : Not available.

**Partition coefficient: n-octanol/water** : Not available.

**Auto-ignition temperature** : Not available.

**Decomposition temperature** : Not available.

**SADT** : Not available.

**Viscosity** : Not available.

## Section 10. Stability and reactivity

**Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

**Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

## Section 10. Stability and reactivity

**Incompatible materials** : Reactive or incompatible with the following materials:  
oxidizing materials

**Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**Hazardous polymerization** : Under normal conditions of storage and use, hazardous polymerization will not occur.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
isopentane	LC50 Inhalation Vapor	Rat	280000 mg/m <sup>3</sup>	4 hours
n-pentane	LC50 Inhalation Vapor	Rat	364 g/m <sup>3</sup>	4 hours
cyclopentane	LD50 Oral	Rat	11400 mg/kg	-

#### Irritation/Corrosion

Not available.

#### Sensitization

Not available.

#### Mutagenicity

Not available.

#### Carcinogenicity

Not available.

#### Reproductive toxicity

Not available.

#### Teratogenicity

Not available.

#### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
isopentane	Category 3	Not applicable.	Narcotic effects
2,3-dimethylbutane	Category 3	Not applicable.	Narcotic effects
n-pentane	Category 3	Not applicable.	Narcotic effects
2-methylpentane	Category 3	Not applicable.	Narcotic effects
3-methylpentane	Category 3	Not applicable.	Narcotic effects
2,2-dimethylbutane	Category 3	Not applicable.	Narcotic effects

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Name	Result
isopentane	ASPIRATION HAZARD - Category 1
2,3-dimethylbutane	ASPIRATION HAZARD - Category 1
3-methylpentane	ASPIRATION HAZARD - Category 1

**Information on the likely routes of exposure** : Not available.

## Section 11. Toxicological information

### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.

**Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness.

**Skin contact** : Causes skin irritation.

**Ingestion** : Can cause central nervous system (CNS) depression.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:, pain or irritation, watering, redness

**Inhalation** : Adverse symptoms may include the following:, nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, unconsciousness

**Skin contact** : Adverse symptoms may include the following:, irritation, redness

**Ingestion** : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

**General** : No known significant effects or critical hazards.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : No known significant effects or critical hazards.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Not available.

## Section 12. Ecological information

### Toxicity

Not available.

### Persistence and degradability

Not available.

### Bioaccumulative potential

## Section 12. Ecological information

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
isopentane	3	171	low
2,3-dimethylbutane	3.42	-	low
n-pentane	3.45	171	low
cyclopentane	3	70.8	low
3-methylpentane	3.6	-	low
2,2-dimethylbutane	3.82	-	low

### Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

### Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	DOT	TDG	Mexico	IMDG	IATA
<b>UN number</b>	UN3161	UN3161	UN3161	UN3161	UN3161
<b>UN proper shipping name</b>	Liquefied gas, flammable n.o.s. (2-methylpentane, isopentane)	Liquefied gas, flammable n.o.s. (2-methylpentane, isopentane)	Liquefied gas, flammable n.o.s. (2-methylpentane, isopentane)	Liquefied gas, flammable n.o.s. (2-methylpentane, isopentane)	Liquefied gas, flammable n.o.s. (2-methylpentane, isopentane)
<b>Transport hazard class(es)</b>	2.1  	2.1  	2.1 	2.1  	2.1 
<b>Packing group</b>	-	-	-	-	-
<b>Environment</b>	No.	No.	No.	Yes.	No.
<b>Additional information</b>	This product is not regulated as a marine pollutant when transported on inland waterways in sizes of $\leq 5$ L or $\leq 5$ kg or by road, rail, or inland air in non-bulk sizes, provided the packagings meet the general provisions of §§ 173.24 and 173.24a.	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2), 2.7 (Marine pollutant mark).  The marine pollutant mark is not required when transported by road or rail.  <u>Explosive Limit and Limited Quantity Index</u>	-	The marine pollutant mark is not required when transported in sizes of $\leq 5$ L or $\leq 5$ kg.	The environmentally hazardous substance mark may appear if required by other transportation regulations.

## Section 14. Transport information

		<p>0.125</p> <p><u>ERAP Index</u> 3000</p> <p><u>Passenger Carrying Ship Index</u> Forbidden</p> <p><u>Passenger Carrying Road or Rail Index</u> Forbidden</p>		
--	--	--	--	--

**“Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the product.”**

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** : Not available.

## Section 15. Regulatory information

**U.S. Federal regulations** : **TSCA 8(a) PAIR:** pentane; cyclopentane  
**TSCA 8(a) CDR Exempt/Partial exemption:** Not determined  
**United States inventory (TSCA 8b):** All components are listed or exempted.  
**Clean Air Act (CAA) 112 regulated flammable substances:** pentane; Isopentane (2-Methylbutane)

**Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Not listed

**Clean Air Act Section 602 Class I Substances** : Not listed

**Clean Air Act Section 602 Class II Substances** : Not listed

**DEA List I Chemicals (Precursor Chemicals)** : Not listed

**DEA List II Chemicals (Essential Chemicals)** : Not listed

### SARA 302/304

#### Composition/information on ingredients

No products were found.

**SARA 304 RQ** : Not applicable.

### SARA 311/312

**Classification** : Fire hazard  
 Immediate (acute) health hazard

#### Composition/information on ingredients

## Section 15. Regulatory information

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
isopentane	40 - 50	Yes.	No.	No.	Yes.	No.
2,3-dimethylbutane	20 - 21	Yes.	No.	No.	Yes.	No.
n-pentane	15 - 16	Yes.	No.	No.	Yes.	No.
cyclopentane	14 - 15	Yes.	No.	No.	No.	No.
2-methylpentane	7 - 8	Yes.	No.	No.	Yes.	No.
3-methylpentane	0.5 - 0.9999	Yes.	No.	No.	Yes.	No.
2,2-dimethylbutane	0.1 - 0.9999	Yes.	No.	No.	Yes.	No.

### State regulations

**Massachusetts** : The following components are listed: PENTANE; ISOPENTANE; CYCLOPENTANE; 2,3-DIMETHYLBUTANE; ISOHEXANE

**New York** : None of the components are listed.

**New Jersey** : The following components are listed: PENTANE; ISOPENTANE; BUTANE, 2-METHYL-; CYCLOPENTANE; 2,3-DIMETHYLBUTANE; BUTANE, 2,3-DIMETHYL-; 2-METHYLPENTANE; ISOHEXANE

**Pennsylvania** : The following components are listed: PENTANE; BUTANE, 2-METHYL-; CYCLOPENTANE; BUTANE, 2,3-DIMETHYL-; PENTANE, 2-METHYL-

### International regulations

#### International lists

#### National inventory

**Australia** : All components are listed or exempted.

**Canada** : All components are listed or exempted.

**China** : All components are listed or exempted.

**Europe** : All components are listed or exempted.

**Japan** : All components are listed or exempted.

**Malaysia** : Not determined.

**New Zealand** : All components are listed or exempted.

**Philippines** : All components are listed or exempted.

**Republic of Korea** : All components are listed or exempted.

**Taiwan** : All components are listed or exempted.

#### Canada

##### **WHMIS (Canada)**

: Not controlled under WHMIS (Canada).

**CEPA Toxic substances**: None of the components are listed.

**Canadian RET**: None of the components are listed.

**Canadian NPRI**: The following components are listed: Pentane (all isomers); Pentane (all isomers); Hexane; Hexane

**Alberta Designated Substances**: None of the components are listed.

**Ontario Designated Substances**: None of the components are listed.

**Quebec Designated Substances**: None of the components are listed.

## Section 16. Other information

**Canada Label requirements** : Not controlled under WHMIS (Canada).

### Hazardous Material Information System (U.S.A.)

Health	1
Flammability	4
Physical hazards	3

## Section 16. Other information

**Caution:** HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

### National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

### Procedure used to derive the classification

Classification	Justification
Flam. Liq. 1, H224	Expert judgment
Skin Irrit. 2, H315	Expert judgment
STOT SE 3, H336	Calculation method
Aquatic Chronic 2, H411	Calculation method

### History

<b>Date of printing</b>	:	4/10/2017
<b>Date of issue/Date of revision</b>	:	4/10/2017
<b>Date of previous issue</b>	:	No previous validation
<b>Version</b>	:	1
<b>Key to abbreviations</b>	:	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
<b>References</b>	:	Not available.

► Indicates information that has changed from previously issued version.

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.